

VP1656 - 15.6" 1920X1200P PORTABLE MONITOR WITH 40W USB-C, STAND, CARRYING CASE, PANTONE VALIDATED

Key **Features**






16"
DISPLAY



IPS
PANEL



1920 X 1200
RESOLUTION



Product **Description**

The ViewSonic® ColorPro® VP1656 is a 16” portable monitor that boasts a native WUXGA 1920 x 1200 resolution. Featuring a flexible and foldable ergonomic stand, it offers easy height adjustment to achieve the perfect viewing angle across various environments. This monitor is Pantone Validated and comes factory hardware calibrated, with 100% sRGB color gamut ensuring richer color uniformity and enhanced detail accuracy to meet the high standards of professional content creators. An integrated tripod mount in the stand allows the display to function as a high-quality photo or video preview screen, ideal for fine adjustments in the field. Versatile connectivity options include two USB-C ports supporting 2-way charging, a micro HDMI port, and a headphone jack.

Specifications


More Information	
UPC	766907029888
Screen Size	16"
Viewable Area (in.)	16
Panel Type	IPS
Display Resolution	1920 x 1200
Display Resolution	WUXGA (1920x1200)
Static Contrast Ratio	1,200:1
Dynamic Contrast Ratio	20,000,000:1
Light Source	LED
Brightness	300 cd/m2
Color Space Support	8 bit true
Aspect Ratio	16:10
Response Time (Typical GTG)	6.5ms
Viewing Angles	170º horizontal, 170º vertical
Backlight Life (Hours)	15,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate	75Hz
PC Resolution (max)	1920 X 1200
Mac® Resolution (max)	1920 X 1200
USB Type C	40W x 2
3.5mm Audio Out	1
Micro HDMI	1
Internal Speakers	1W (x2)
Eco Mode (Conserve)	7.0
Eco Mode (optimized)	7.8W
Consumption (typical)	8.6W
Consumption (max)	17.0W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5
Power Supply	External
Cable Organization	No
Physical Controls	Up, Down, Left/Return, Right/Confirmed, Power
On Screen Display	Input Select, Color Mode, ViewMode, Audio Adjust, Setup Menu

Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
Frequency Horizontal	micro HDMI 1.4, USB Type C: 24 ~ 95 KHz
Frequency Vertical	micro HDMI 1.4, USB Type C: 24 ~ 75 Hz
Height Adjust	76 mm
Tilt (Forward/Back)	55º / 20º
Regulations	cTUVus, FCC-B ICES003, Energy Star, EPEAT, CEC, NRCan, NOM, Mexico Energy
Net (lbs)	3.4
Gross (lbs)	7.1
Net (kg)	1.6
Gross (kg)	3.2
Packaging (in.)	16.7 x 12.4 x 5.1
Physical (in.)	14.33 x 9.43~12.89 x 0.91
Packaging (mm)	425.0 x 316.0 x 129.0
Physical (mm)	363.88 x 239.52~327.32 x 23.15
Package Contents	VP1656 Display, Power adaptor, USB-C to USB-A cable, micro HDMI Cable, USB-C Cable, Quick Start Guide, Protective bag
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907029888







Contact Sales
ViewSonic.com
888.881.8781
email:
salesinfo@viewsonic.com