

VIEWSONIC 27" 4K COLORPRO MONITOR WITH 90W USB-C ADOBE RGB AND DCI-P3 COLOR GAMUT | VP2786A-4K

Key Features


- **PANTONE VALIDATED DISPLAY:** Certified to deliver true Pantone color accuracy for creative professionals.
- **PRECISE COLOR COVERAGE:** 100% Adobe RGB and 98% DCI-P3 ensure exact, lifelike color reproduction.
- **AMAZING COLOR ACCURACY:** Factory calibrated to Delta E<2 for professional photo, video, and design work.
- **EXCELLENT SCREEN UNIFORMITY:** Built-in uniformity function ensures consistent color and brightness edge-to-edge.
- **SINGLE-CABLE SIMPLICITY:** USB-C transfers data, audio, video, and 90W charging with one cable.



27"
DISPLAY



IPS
PANEL



3840 X 2160
RESOLUTION



Product Description

The ViewSonic® ColorPro™ VP2786A-4K is a 27" professional monitor that delivers outstanding visual performance and exceptional color accuracy. With 3840 x 2160 Ultra HD resolution, true 10-bit color, and color coverage of 100% Adobe RGB and 98% DCI-P3, the VP2786A-4K showcases your work with incredible color fidelity. Certifications from Fogra and G7 ensure high-quality print performance, making it ideal for color-critical workflows. USB-C connectivity simplifies your workspace by delivering audio, video, data, and up to 90W of power over a single universal cable. To ensure precise, uniform color, each monitor is factory calibrated to achieve an impressive Delta E<2 value. With its sleek design, advanced technology, and intuitive user interface, the VP2786A-4K meets the demands of professional content creators.

Specifications

More Information

UPC	766907029734
Screen Size	27"
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	3840 x 2160
Display Resolution	4K (3840x2160)
Static Contrast Ratio	1,300:1
Dynamic Contrast Ratio	20,000,000:1

Light Source	LED
Brightness	350 cd/m2
Colors	1.07B
Color Space Support	10 bit true
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
PC Resolution (max)	3840 X 2160
Mac® Resolution (max)	3840 X 2160
USB Type A	4
USB Type B	1
USB Type C	90W x 1
Mini USB	1
3.5mm Audio Out	1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	3W (x2)
Eco Mode (Conserve)	67
Eco Mode (optimized)	77
Consumption (typical)	89
Consumption (max)	92
Voltage	100-240 VAC, 50-60Hz
Stand-by	0.5
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Joystick key: Up, Right, Down, Left, Center; Power
On Screen Display	Input Select, Color Model, ViewMode, Audio Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 204 KHz
Frequency Vertical	24 ~ 120 Hz
Height Adjust	130 mm / 5.1 in

Swivel	120°
Pivot (Right/Left)	90° / 90°
Tilt (Forward/Back)	3° / 21°
Regulations	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, NOM, Mexico Energy
Net (lbs)	18.4
Net Without Stand (lbs)	10.8
Gross (lbs)	29
Net (kg)	8.3
Net Without Stand (kg)	4.9
Gross (kg)	13.2
Packaging (in.)	27.2 " (W) x 19.9 " (H) x 8.9 " (D)
Physical (in.)	24.1 " (W) x 17.68~22.41 " (H) x 9.1 " (D)
Physical Without Stand (in.)	24.1 " (W) x 14.1 " (H) x 2.2 " (D)
Packaging (mm)	692 mm (W) x 505 mm (H) x 225 mm (D)
Physical (mm)	613 mm (W) x 449.11~569.11 mm (H) x 232 mm (D)
Physical Without Stand (mm)	613 mm (W) x 358 mm (H) x 55 mm (D)
Package Contents	LCD Display, Power Cable, USB-C Cable, HDMI cable, USB-A/B Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907029734



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com