



## 136" ALL-IN-ONE DIRECT VIEW LED DISPLAY | LDE136G-152

## Key Features

- **INNOVATIVE ALL-IN-ONE DESIGN:** Simplified setup includes everything needed already built into cabinets.
- **OUTSTANDING PRICE-PERFORMANCE:** High-impact dvLED technology that maximizes your investment.
- **GLUE-ON-BOARD TECHNOLOGY:** Protects LEDs from damage and moisture in high-traffic environments.
- **SIMPLIFIED OS:** Streamlines setup, operation, and security.
- **HOT-SWAPPABLE MODULES:** Easy front-serviceable maintenance and includes spare tiles.

136  
DISPLAYDirect View LED SMD + Glue-on-Board  
PANEL3840x2160  
RESOLUTION

## Product Description

The ViewSonic® LDE136G-152 is a 136" all-in-one Direct View LED (dvLED) display. It's part of our LDE Series, designed to deliver outstanding price-performance and simplified dvLED technology. This line is perfect for schools and businesses seeking a high-impact solution that maximizes their investment. The LDE136G-152 features an innovative, fully integrated All-in-One design with a simplified OS. Everything you need is built directly into the cabinets, which allows for easier installation and operation. The complete solution ships together and can be ordered with a single SKU, making setup a breeze. This display is also built to last. It uses durable Glue-on-Board technology with an IP54 dust and moisture rating and an IK06 impact rating. You can confidently use it in busy lobbies, classrooms, or conference rooms. With 600-nit brightness and a 6,500:1 contrast ratio, it delivers a vivid, exceptional viewing experience, representing a premier value in large-format displays.

## Specifications

### More Information

<b>UPC</b>	766907038156
<b>CPU</b>	RK3588
<b>CPU</b>	RK3588
<b>Internal Speakers</b>	8W (x2)
<b>PC Resolution (max)</b>	3840x2160
<b>Mac® Resolution (max)</b>	3840x2160
<b>HDMI 2.0 (with HDCP 2.2)</b>	1
<b>HDMI 1.4 (with HDCP 1.4)</b>	1
<b>HDMI 1.4 Out (with HDCP 1.4)</b>	1

<b>3.5mm Audio Out</b>	1
<b>USB 3.0</b>	2
<b>RS232</b>	1
<b>Ethernet LAN (RJ45)</b>	1
<b>Voltage</b>	100-120V/20A ~ 50/60Hz
<b>Consumption (max)</b>	1600W
<b>Consumption (typical)</b>	533W
<b>Stand-by</b>	<0.5W
<b>On Screen Display</b>	Yes
<b>Remote Control</b>	Yes
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Humidity (non-condensing)</b>	20-80%
<b>Physical (in.)</b>	118.58 x 67.28 x 2.05
<b>Physical with Wall Mount (in.)</b>	118.58 x 67.28 x 2.43
<b>Physical (mm)</b>	3012 x 1708.9 x 52
<b>Physical with Wall Mount (mm)</b>	3012 x 1708.9 x 61.7
<b>Package Contents</b>	Power Cord, LAN Cable, Remote Control, Installation Guide, Wall Mount, LD-MK-004, LD-MK-006
<b>Regulations</b>	cTUVus, FCC, RoHS
<b>Display Type</b>	Direct View LED
<b>Screen Size</b>	136
<b>Light Source</b>	DLED
<b>LED Pitch Size (mm)</b>	1.56
<b>LED Grayscale</b>	13 bit
<b>Display Resolution</b>	1920 x 1080
<b>Refresh Rate</b>	3,840Hz
<b>Panel Type</b>	Direct View LED SMD + Glue-on-Board
<b>Aspect Ratio</b>	16:9
<b>Static Contrast Ratio</b>	6,500:1
<b>Backlight Life (Hours)</b>	100,000
<b>Brightness</b>	600-nit
<b>Viewing Angles</b>	170° horizontal, 170° vertical
<b>Impact Protection Rating</b>	IK06 (Front)
<b>Operation Rating</b>	24/7

UPC: 766907038156



**Contact Sales**

[ViewSonic.com](http://ViewSonic.com)

888.881.8781

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)