


163" ALL-IN-ONE DVLED DISPLAYS | LDE163-183

Key Features


- **INNOVATIVE ALL-IN-ONE DESIGN:** Power, controls and image stitching are built directly into the cabinet for simplified installation and operation
- **PRICE-PERFORMANCE:** A single-SKU, All-in-One design lowers installation costs and total cost of ownership
- **BUILT TO LAST:** Glue-on-Board technology with IP65 and IK06 ratings help protect against damage and moisture in high-traffic environments
- **SIMPLIFIED OS:** True plug-and-play operation gets the display up and running in seconds
- **INTEGRATED AV MANAGEMENT:** Q-SYS, Crestron, Extron and AMX compatibility enable centralized control of the AV ecosystem
- **EASY MAINTENANCE:** Hot-swappable front modules and included spare tiles help minimize downtime



163"
DISPLAY



PANEL



RESOLUTION



Product Description

The 163" All-in-One ViewSonic® LDE163-183 Direct View LED (dvLED) display is built for organizations that need high-impact messaging without the cost or complexity of a custom video wall. Power, controls and image processing are already built into the cabinets, so the display ships and installs as a single SKU instead of a multi-part system. A simplified OS gets the display from power-on to full operation in seconds. Durable Glue-on-Board construction, backed by an IP65 dust and moisture rating and an IK06 impact rating, holds up in busy lobbies, classrooms and conference rooms. At 600-nit brightness and a 6,500:1 contrast ratio, the display maintains sharp, vivid image quality even in well-lit spaces.

Specifications

More Information


UPC

766907042726

OS	Simplified OS
CPU	RK3588
Internal Speakers	15W (x2)
HDMI 2.0 (with HDCP 2.2)	1
HDMI 1.4 (with HDCP 1.4)	1
HDMI 1.4 Out	1
3.5mm Audio Out	1
USB Type A	2 (USB 3.0, internal x 1, internal x 1)
USB 3.0	2
RS232	1
Ethernet LAN (RJ45)	1
Voltage	100-120V/20A ~ 50/60Hz
Consumption (max)	2060W
Consumption (typical)	669W
Stand-by	<0.5W
Remote Control	Yes
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-80%
Net (lbs)	331
Gross (lbs)	650
Net (kg)	150.1
Gross (kg)	295.0
Packaging (in.)	89.76 x 42.52 x 47.24
Physical (in.)	142.2 x 80.55 x 2.04
Physical with Wall Mount (in.)	142.2 x 80.55 x 2.43
Packaging (mm)	2280.0 x 1080.0 x 1200.0
Physical (mm)	3612.0 x 2046.4 x 52.0
Physical with Wall Mount (mm)	3612.0 x 2046.4 x 61.7
Warranty	3-year limited warranty
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Package Contents	Power Cord, LAN Cable, Remote Control, Installation Guide, Wall Mount, LD-MK-004, LD-MK-006
Regulations	cTUVus, FCC, RoHS
Display Type	Direct View LED
Technology	Direct View LED SMD + Glue-on-Board
Screen Size	163"
LED Pitch Size (mm)	1.88

LED Grayscale	13 bits
Display Resolution	1920 x 1080
Refresh Rate	3,840Hz
Aspect Ratio	16:9
Static Contrast Ratio	6,500:1
Brightness	600 nits (100 levels adjustable)
Viewing Angles	170º horizontal, 170º vertical
Impact Protection Rating	IK06 (Front)

UPC: 766907042726



Contact Sales
ViewSonic.com
888.881.8781
email:
salesinfo@viewsonic.com