ViewSonic

27" QHD IPS VIDEO CONFERENCING MONITOR WITH 5MP WINDOWS HELLO CERTIFIED WEBCAM, 100W USB-C, RJ45 | VG2758V-2K

Key **Features**

- VERSATILE MONITOR: 27 Inch QHD (2560 x 1440) IPS monitor with thin bezels and 100Hz refresh rate
- VIDEO CONFERENCING MONITOR: Built-in 5MP webcam, microphone with background noise reduction, and dual 5W speakers
- DITCH THE DOCK: USB-C with 100W power delivery, video, and data, plus RJ45 Ethernet and a USB hub, all over one cable
- FLEXIBLE CONNECTIVITY: Supports PC, Mac and more with USB-C, HDMI 2.1, DisplayPort 1.4, and USB Type-A
- ERGONOMIC STAND: Advanced ergonomics (tilt, swivel, pivot, and 150 mm height adjustment) for all-day comfort



27"
DISPLAY



IPS
PANEL



2560 x 1440
RESOLUTION

Product **Description**

Built for the modern office, the ViewSonic® VG2758V-2K turns any desk into a fully equipped video conferencing workstation with an integrated docking hub, 5MP webcam, microphone, and dual 5W speakers. A single USB-C cable connects your laptop, delivers up to 100W of power, and carries video and data, while the built-in RJ45 Ethernet port provides a stable wired network connection. A second USB-C port daisy chains an additional monitor for a streamlined dual-screen setup. The 27-inch QHD (2560 x 1440) IPS display with a 100Hz refresh rate delivers sharp, fluid visuals for documents, spreadsheets, and multitasking. Windows Hello certified sign-in and background noise reduction make every log-in and meeting smoother, and a fully adjustable stand with tilt, swivel, pivot, and 150 mm height adjustment supports all-day comfort. For businesses standardizing across a hybrid workforce, the VG2758V-2K means one monitor, one cable, and one less thing for IT to manage.

Specifications

	More Information
UPC	766907041859
Screen Size	27"
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	QHD (2560x1440)
Static Contrast Ratio	1,500:1
Dynamic Contrast Ratio	80,000,000:1

Light Source	LED
Brightness	300 cd/m2
Colors	16.7M
Color Space Support	8 bit (6 bit + Hi-FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate	100Hz
PC Resolution (max)	2560 x 1440
Mac® Resolution (max)	2560 x 1440
USB Type A	3
USB Type C	3
3.5mm Audio Out	1
Ethernet LAN (RJ45)	1
HDMI 2.1 In	1
DisplayPort	1
Internal Speakers	5W (x2)
Eco Mode (Conserve)	134W
Eco Mode (optimized)	137W
Consumption (typical)	140W
Consumption (max)	202W
Voltage	100-240 VAC, 50-60Hz
Stand-by	0.5W
Power Supply	Internal
Cable Organization	Yes
Kensington Lock Slot	1
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI 2.1, DisplayPort, USB Type C: 30-151 kHz
Frequency Vertical	HDMI 2.1, DisplayPort, USB Type C: 50-100 Hz
Height Adjust	150 mm / 5.9 in
Swivel	90º
Pivot (Right/Left)	90º / 90º
Tilt (Forward/Back)	5º / 30º
Regulations	cSGSus, FCC-B, ICES003, Energy Star 8.0, EPEAT, CEC

Net (lbs)	14.77
Net Without Stand (lbs)	9.48
Gross (lbs)	21.72
Net (kg)	6.70
Net Without Stand (kg)	4.30
Gross (kg)	9.85
Packaging (in.)	27.95 x 5.71 x 18.31
Physical (in.)	24.1 x 15.88 ~21.4 x 8.08
Physical Without Stand (in.)	24.0 x 14.9 x 2.14
Packaging (mm)	709.93 x 145.03 x 465.07
Physical (mm)	612.84 x 403.36~543.9 x 205.27
Physical Without Stand (mm)	612.84 x 379.11 x 54.59
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907041859

Contact Sales

ViewSonic.com
888.881.8781
email: salesinfo@viewsonic.com