

VA2756-MHD - 27" 1080P IPS MONITOR WITH FREESYNC, HDMI, DISPLAYPORT, AND VGA


Key Features

REFURBISHED


- 27 Inch Full HD (1920x1080p) IPS monitor with thin bezels and 100Hz refresh rate
- Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- Adaptive Sync technology enables smooth frame rates to aid you in battle
- Optimized view settings offer "Game," "Movie," "Web," "Text," and "Mono" presets
- The VA2756-MHD supports laptops, PCs, Macs and more with HDMI, DisplayPort and VGA inputs




Future Proof inputs for flexible connectivity options



27
DISPLAY



IPS
PANEL



1920 x 1080
RESOLUTION



Product Description


With future-proof connectivity, the ViewSonic® VA2756-mhd is a productivity-boosting monitor perfect for business applications. Designed with SuperClear® IPS panel technology for wide-angle viewing and incredibly vivid colors, this monitor also features a 3-sided frameless design for a seamless viewing experience in multi-monitor setups. Extensive connectivity options include VGA, HDMI, and DisplayPort so that you can connect to a variety of HD and analog devices – today and tomorrow. In addition, Flicker-Free technology and a Blue Light Filter help to minimize eye strain from extended viewing periods. With ViewSonic's industry-leading 3-year limited warranty, this monitor is a solid long-term investment for enterprise and home applications.

Specifications

	More Information
UPC	766907984910
Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	1920 x 1080
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Color Space Support	6 bits + Hi FRC
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	7ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
Refresh Rate	100Hz
PC Resolution (max)	1920 x 1080
Mac® Resolution (max)	1920 x 1080
3.5mm Audio In	1
3.5mm Audio Out	1
VGA	1
HDMI 1.4 In	1
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	14W
Eco Mode (optimized)	18W
Consumption (typical)	23W
Consumption (max)	32W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	Internal

Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key Buttons 1, 2, 3, 4, 5, 6 (Power)
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI: 15 ~ 83KHz, DP: 24 ~ 83KHz
Frequency Vertical	HDMI: 50 ~ 75Hz, DP: 50 ~ 75Hz
Digital Sync	TMDS for HDMI, PCI-E for DisplayPort
Tilt (Forward/Back)	4° / 20°
Regulations	cULus, FCC-B, ICES003, Energy Star 8.0, EPEAT, Mexico Energy, MX-CoC
Net (lbs)	10.9
Net Without Stand (lbs)	9.1
Gross (lbs)	15.0
Net (kg)	4.9
Net Without Stand (kg)	4.1
Gross (kg)	6.8
Packaging (in.)	26.7 x 19.6 x 6.5
Physical (in.)	24.1 x 16.9 x 9.2
Physical Without Stand (in.)	24.1 x 14.4 x 2.0
Packaging (mm)	677.0 x 497.0 x 164.0
Physical (mm)	611.3 x 429.0 x 232.9
Physical Without Stand (mm)	611.3 x 366.5 x 51.6
Package Contents	VA2756-mhd Display, Power Cable, HDMI to HDMI (1.5m), Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907984910



Contact Sales
ViewSonic.com
 888.881.8781
 email:
salesinfo@viewsonic.com