

# VP2756-2K - 27" COLORPRO™ 1440P IPS MONITOR WITH 60W USB C, SRGB AND PANTONE VALIDATED

## Key Features


---



27"  
DISPLAY



IPS  
PANEL



2560 x 1440  
RESOLUTION



## Product Description

---

Engineered to deliver unmatched color accuracy crucial for professional applications, the ViewSonic® VP2756-2K QHD monitor displays your work with the vivid and lifelike color it deserves. With a SuperClear® IPS panel and a sleek 3-sided frameless design, the VP2756-2K provides a near-seamless viewing experience ideal for multi-monitor setups. The VP2756-2K is equipped with USB-C for single cable connectivity to deliver video, audio, and 60W of power delivery. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E <2, so you can be confident what you see on screen is what your clients and customers will see as well.


## Specifications

---

<b>UPC</b>	766907017601
<b>Screen Size</b>	27"
<b>Viewable Area (in.)</b>	27
<b>Panel Type</b>	IPS
<b>Display Resolution</b>	2560 x 1440
<b>Display Resolution</b>	WQHD (2560x1440)
<b>Static Contrast Ratio</b>	1,000:1
<b>Dynamic Contrast Ratio</b>	20,000,000:1
<b>Light Source</b>	LED
<b>Brightness</b>	350 cd/m2
<b>Colors</b>	16.7M
<b>Color Space Support</b>	8 bit
<b>Aspect Ratio</b>	16:9
<b>Response Time (Typical GTG)</b>	5ms
<b>Viewing Angles</b>	178° horizontal, 178° vertical
<b>Backlight Life (Hours)</b>	30,000
<b>Panel Surface</b>	Anti-Glare type, Hard-coating (3H), Haze 25%
<b>PC Resolution (max)</b>	2560 x 1440
<b>Mac® Resolution (max)</b>	2560 x 1440
<b>USB Type A</b>	2
<b>USB Type B</b>	1
<b>USB Type C</b>	60W x 1
<b>HDMI 1.4 In</b>	1
<b>DisplayPort</b>	1
<b>Eco Mode (Conserve)</b>	34.5W
<b>Eco Mode (optimized)</b>	38.5W
<b>Consumption (typical)</b>	40W
<b>Consumption (max)</b>	121W
<b>Voltage</b>	100-240 VAC
<b>Stand-by</b>	0.3W
<b>Power Supply</b>	Internal
<b>Cable Organization</b>	No
<b>Kensington Lock Slot</b>	1
<b>Physical Controls</b>	Key 1 (power), Key 2, Key 3, Key 4, Key 5 (favorite)
<b>On Screen Display</b>	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
<b>Temperature</b>	32-104° F (0 - 40° C)

<b>Humidity (non-condensing)</b>	20-90%
<b>VESA Compatible</b>	100 x 100 mm
<b>Frequency Horizontal</b>	15 ~ 130 KHz
<b>Frequency Vertical</b>	24 ~ 75 Hz
<b>Height Adjust</b>	130 mm / 5.1 in
<b>Swivel</b>	60°
<b>Pivot (Right/Left)</b>	90° / 90°
<b>Regulations</b>	cTUVus, FCC-B, ICES003, CEC, MX-CoC, Mexico Energy
<b>Net (lbs)</b>	15.1
<b>Net Without Stand (lbs)</b>	9.8
<b>Gross (lbs)</b>	21.0
<b>Net (kg)</b>	6.9
<b>Net Without Stand (kg)</b>	4.4
<b>Gross (kg)</b>	9.5
<b>Packaging (in.)</b>	29.1 x 18.3 x 8.9
<b>Physical (in.)</b>	24.1 x 16.15~21.27 x 8.5
<b>Physical Without Stand (in.)</b>	24.1 x 14.3 x 2.1
<b>Packaging (mm)</b>	740.0 x 465.0 x 225.0
<b>Physical (mm)</b>	613.0 x 410.0~540.0 x 215.0
<b>Physical Without Stand (mm)</b>	613.0 x 363.0 x 53.0
<b>Package Contents</b>	VP2756-2K, Power Cable, USB-C Cable, HDMI cable, UAB-A/B Cable
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.
<b>Warranty</b>	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907017601



**Contact Sales**  
**[ViewSonic.com](https://www.viewsonic.com)**

888.881.8781

email:

[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)