

PJD7820HD-S


Key Features



30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



VGA to 1920x1200
RESOLUTION



Product Description

The ViewSonic PJD7820HD is the best in class price-performance Full HD 1080p DLP projector with 3,000 ANSI lumens and 15,000:1 contrast ratio. This projector is packed with features including HDMI, 3D Blu-ray ready, multiple PC and video input options, 1.3x optical zoom, keystone correction, DynamicEco and integrated speaker. With the latest HDMI, the PJD7820HD can now display 3D images from 3D Blu-ray players. DynamicEco allows user to put the projector in "standby" energy saving mode by reducing brightness down to 30% when the projector is not in use or without waiting for the projector to restart. Filter-less design and energy-saving eco-mode provide for virtually zero maintenance and product reliability. The ViewSonic PJD7820HD Full HD 3D 1080p projector is perfect for home, home office and small office.

Specifications

	More Information
UPC	766907881912
Light Source	DLP Lamp
Display Resolution	Full HD (1920x1080)
Display Resolution	1920 x 1080
Brightness (Lumens)	3,000 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	2.5 - 25.0 ft. / 0.8 - 7.6 m
Throw Ratio	1.15~1.5
Keystone	Manual vertical digital keystone correction ($\pm 40^\circ$)
Lens	1.3x Manual optical zoom / manual optical focus
Light Source (watt)	210
Light Source Life, Normal (hours)	4000
Light Source Life, Dynamic Eco-Mode (hours)	6000

Color Depth	30 bits, 1.07B Color (10+10+10)
Aspect Ratio	16:9
Frequency Horizontal	31-100KHz
Frequency Vertical	48-120Hz
PC Resolution (max)	VGA to 1920x1200
Mac® Resolution (max)	p to 1920x1200 (may require MAC adapter)
3.5mm Audio Out	1
3.5mm Audio In	1
HDMI In	1
Composite RCA Video In	1
S-Video In	1
Mini USB	1
RGB Input	15-pin mini D-sub (x2)
Internal Speakers	2W (x1)
Voltage	100~240VAC (Auto Switching), 50-60Hz (universal)
Consumption (typical)	260W
Stand-by	<0.5W
Physical Controls	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display	Display, Picture, Source, System Setup (Basic), System Setup (Advanced), Information
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	10-90%
Normal	35dB
Eco-Mode	29dB
Kensington Lock Slot	1
Net Without Stand (lbs)	4.6
Gross (lbs)	7.5
Net Without Stand (kg)	2.1
Gross (kg)	3.4
Packaging (in.)	14.2 x 12.8 x 7.4
Physical Without Stand (in.)	10.6 x 3.3 x 8.7
Packaging (mm)	360 x 325 x 188
Physical Without Stand (mm)	268 x 84.4 x 221
Regulations	CB, UL, cUL, FCC (including ICES-003), CE, UL-Argentina, NOM, GS, GOST-R, SASO, Ukraine, PSB, C-Tick, Korean-KC, CCC, CECP, WEEE, RoHS
Package Contents	PJD7820HD projector, power cable, VGA cable, remote control with batteries, Quick Start Guide, ViewSonic Wizard DVD (with User Guide)

Warranty

*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

Recycle/Disposal

Please dispose of in accordance with local, state or federal laws.

Classification

Discontinued

UPC: 766907881912



Contact Sales

ViewSonic.com

888.881.8781 

email: salesinfo@viewsonic.com 