



PJD6353S-S


Key Features



30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



VGA to UXGA
RESOLUTION



Product Description

The ViewSonic PJD6353s is an advanced short throw, networkable DLP projector equipped with Crestron built-in e-Control and RoomView Express, making it the perfect projector for classroom and corporate environments. With its short throw lens, the projector can project a 50" image from only 2 feet away. In addition, the projector is AMX Device Discovery certified which makes it a robust network projector for any size campus or business. The PJD6353s delivers amazingly clear images with XGA 1024x768 native resolution, 2500 ANSI lumens and 15,000:1 high contrast ratio, while BrilliantColor technology provides vivid, vibrant colors. With the new DynamicEco technology, presenters can control audiences' focus by dimming the brightness to 30% with a simple click of the remote. The PJD6353s comes standard with multiple PC and video inputs including HDMI, 120Hz/3D-Ready and 10w integrated speaker which provide amazing multimedia performance. The PJD6353s short throw, networkable XGA DLP projector delivers top class performance and value for both education and businesses.

Specifications

More Information

UPC

766907654127

Light Source	DLP Lamp
Display Resolution	XGA (1024x768)
Display Resolution	1024 x 768
Brightness (Lumens)	2,500 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	1.22ft-12.15ft / 0.37m-3.7m
Throw Ratio	0.61:1
Keystone	Vertical digital keystone correction: (\pm 40°)
Lens	Fixed zoom / manual optical focus
Light Source (watt)	180
Light Source Life, Normal (hours)	5000
Light Source Life, Dynamic Eco-Mode (hours)	6000
Color Depth	30 bits, 1.07B Color (10+10+10)
Color Wheel	6-seg RGBCYW
Color Wheel RPM	7200
Aspect Ratio	4:3 (native), 16:9
Frequency Horizontal	31-100KHz
Frequency Vertical	48-120Hz
PC Resolution (max)	VGA to UXGA
Mac® Resolution (max)	Up to SXGA+ (may require MAC adaptor)
HDMI 1.3	1
Ethernet LAN (RJ45)	1
3.5mm Audio Out	1
3.5mm Audio In	2
Control (RS-232)	1
Component RCA	1
Mini USB	1
RGB Input	15-pin mini D- sub (x2)
Internal Speakers	10W (x1)
Voltage	100~240VAC (Auto Switching), 50-60Hz (universal)
Consumption (typical)	310W
Stand-by	<1W
Physical Controls	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display	Display, Picture, Source, System Setup (Basic), System Setup (Advanced), Information
Temperature	32-104° F (0 - 40° C)

Humidity (non-condensing)	10-90%
Normal	32dB
Eco-Mode	29dB
Net Without Stand (lbs)	6.6
Gross (lbs)	9.9
Gross (kg)	4.5
Packaging (in.)	4.2 x 15 x 7.6
Physical Without Stand (in.)	11.6 x 3.3 x 9.5
Packaging (mm)	360 x 380 x 192
Physical Without Stand (mm)	294 x 84 x 242
Regulations	CB, UL, cUL, FCC (including ICES-003), CE, UL-Argentina, NOM, GS, GOST-R, SASO, Ukraine, PSB, C-Tick, Korean-KC, CCC, CECP, WEEE, RoHS
Package Contents	ViewSonic PJD6353s projector, power cable, VGA cable, remote control with batteries, Lens Cap, Quick Start Guide, ViewSonic Wizard DVD (with User Guide).
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Classification	Discontinued

UPC: 766907654127



Contact Sales
ViewSonic.com

888.881.8781
 email:
salesinfo@viewsonic.com