

TD2740-S

Key **Features**






27"
DISPLAY



MVA
PANEL



1920x1080
RESOLUTION



Product **Description**

The ViewSonic TD2740 is an ideal solution for both commercial and consumer touch screen applications. With an intuitive 10-point multi-touch display and full 1080p HD resolution, the 27-inch TD2740 delivers a versatile solution for use in the office or at home, as well as for use as an information kiosk in public areas, or as a teaching tool in interactive learning environments. The bookstand support of the TD2740 provides advanced ergonomics and allows the display to be tilted or laid flat on a tabletop for more comfortable use. SuperClear VAtechnology with ultra-wide viewing angles and 20M:1 MEGA Dynamic Contrast Ratio bring greater definition and clarity to multimedia content. As a complete package, the display also includes a pair of integrated 2W speakers, anHD webcam, and a microphone for video chatting. VGA, HDMI,and DisplayPort inputs provide flexible and future-proof connectivity. Touch the Difference with the ViewSonic TD2740 interactive multi-touch display.

Specifications

More Information

UPC	766907866414
Screen Size	27"

Panel Type	MVA
Display Resolution	1920 x 1080
Static Contrast Ratio	3,000:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	LED
Brightness	260 cd/m2
Response Time (Typical GTG)	12ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	7H Scratch Resistant Surface Hardness
PC Resolution (max)	1920x1080
Mac® Resolution (max)	1920x1080
USB 2.0 Type A	2
3.5mm Audio In	1
3.5mm Audio Out	1
HDMI In	2
VGA	1
HDMI 1.4 In	1
DisplayPort	1
Touch Technology	Capacitive
Touch Points	10-Point Touch
Internal Speakers	2W (x2)
Eco Mode (Conserve)	29W
Eco Mode (optimized)	35W
Consumption (typical)	41W
Voltage	AC 100-240V (universal), 50-60Hz
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1, 2, Down, Up, Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	24~82kHz
Frequency Vertical	50~75Hz

Analog Sync	Separate Sync
Regulations	cULus, FCC, ICES2003, UL-MX-CoC, Mexico Energy, CE, REACH, WEEE, UkrSEPRO
Net (lbs)	19.4
Gross (lbs)	22.5
Net (kg)	8.2
Gross (kg)	10.2
Packaging (in.)	29.1 x 20.1 x 5.0
Physical (in.)	26.5 x 16.5 x 2.0
Packaging (mm)	739 x 510 x 127
Physical (mm)	672.6 x 418.9 x 49.9
Package Contents	TD2740 display, power cable, audio cable, VGA cable, HDMI cable, USB cable, Quick Start Guide, ViewSonic Wizard CD (available in some countries only)
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
Classification	Discontinued

UPC: 766907866414







Contact Sales
ViewSonic.com
888.881.8781
email:
salesinfo@viewsonic.com