


VA2452SM - 24" 1080P LED MONITOR DISPLAYPORT, DVI AND VGA INPUTS

Key Features

- Full HD 1080p resolution
- Stunning color performance & wide-angle viewing
- Flexible connectivity options
- Superior color rendering & intuitive settings
- Enhanced viewing comfort




What's in the box.



24"
DISPLAY



MVA
PANEL



1920 x 1080
RESOLUTION



*Power Cable varies by region



Product Description


The ViewSonic VA2452Sm is a 24" (23.6" viewable) Full HD 1920x1080 LED monitor designed for business applications. With ViewSonic SuperClear MVA panel technology and 3000:1 static contrast ratio, this monitor delivers an incredible front-of-screen work experience at nearly any viewing angle. Versatile input options include future-proof DisplayPort, as well as DVI and VGA inputs, for productivity-boosting connectivity to PC systems, laptops, and other work devices. A matte-finish, uniform bezel design and a VESA-compatible mount adapt easily to multi-monitor or wall-mount set ups, while integrated speakers deliver enhanced multimedia sound. ViewSonic's exclusive ViewMode feature provides intuitive presets that deliver optimized screen performance in different applications. In addition, Flicker-Free technology and a Blue Light Filter help to eliminate eye strain from extended viewing periods for improved productivity. Lastly, a 3-year limited warranty, along with one of the industry's best pixel performance policies, provides great value for the stylish, high-performance VA2452Sm monitor.

Specifications

| | More Information |
|------------------------------------|--|
| UPC | 766907810622 |
| Screen Size | 24" |
| Viewable Area (in.) | 23.6 |
| Panel Type | MVA |
| Display Resolution | 1920 x 1080 |
| Static Contrast Ratio | 3,000:1 |
| Light Source | LED |
| Brightness | 250 cd/m2 |
| Colors | 16.7M |
| Response Time (Typical GTG) | 7ms |
| Viewing Angles | 178° horizontal, 178° vertical |
| Backlight Life (Hours) | 40,000 |
| Panel Surface | 3H Anti-glare, hard-coating |
| PC Resolution (max) | 1920 x 1080 |
| Mac® Resolution (max) | 1920 x 1080 |
| 3.5mm Audio In | 1 |
| 3.5mm Audio Out | 1 |
| VGA | 1 |
| DVI-D | 1 |
| DisplayPort | 1 |
| Internal Speakers | 1.5-watt (x2) |
| Eco Mode (Conserve) | 15W |
| Eco Mode (optimized) | 19W |
| Consumption (typical) | 23W |
| Consumption (max) | 30W |
| Voltage | AC 100-240V (universal), 50-60Hz |
| Cable Organization | No |
| Kensington Lock Slot | 1 |
| Physical Controls | 1, 2, Down, Up, Power |
| On Screen Display | Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall(See user guide for complete OSD functionality) |
| Humidity (non-condensing) | 20-90% |
| VESA Compatible | 100 x 100 mm |

| | |
|-------------------------------------|---|
| Frequency Horizontal | 24~82kHz |
| Frequency Vertical | 50~75Hz |
| Analog Sync | Separate Sync |
| Regulations | cTUVus, FCC-B, ICES003, UL-MX-CoC, Mexico Energy, Reach, WEEE |
| Net (lbs) | 8.6 |
| Net Without Stand (lbs) | 7.8 |
| Gross (lbs) | 11.1 |
| Net (kg) | 3.9 |
| Net Without Stand (kg) | 3.5 |
| Gross (kg) | 5 |
| Packaging (in.) | 24.3 x 16.1 x 4.9 |
| Physical (in.) | 22.2 x 16.6 x 7.8 |
| Physical Without Stand (in.) | 22.2 x 13.2 x 4.9 |
| Packaging (mm) | 616.0 x 409.0 x 124.0 |
| Physical (mm) | 563.0 x 421.7 x 196.8 |
| Physical Without Stand (mm) | 563.0 x 335.0 x 49.5 |
| Package Contents | VA2452Sm monitor, Power cable, DisplayPort cable, Quick Start Guide |
| Recycle/Disposal | Please dispose of in accordance with local, state or federal laws. |
| Warranty | Three-year limited warranty on parts, labor and backlight |

UPC: 766907810622



Contact Sales
ViewSonic.com
 888.881.8781
 email:
salesinfo@viewsonic.com