

PX706HD - 1080P SHORT THROW GAMING PROJECTOR WITH 3000 LUMENS, LOW INPUT LAG AND USB C

Key **Features**






60 - 120 in. / 1.5 - 3.0 m
DISPLAY



PANEL



1920 x 1080
RESOLUTION



Product **Description**

For convenient big screen gaming and entertainment, the ViewSonic® PX706HD projector delivers huge images in small spaces. With a short throw lens, this projector can be placed just a few feet away from a wall or screen, and project an immersive 100” image – making it perfect for big gaming sessions in smaller rooms. 3,000 lumens of brightness and Full HD 1920x1080 resolution provide vivid, ultra-sharp images and graphics, while an ultra-low input latency ensures faster frame-by-frame action and smooth gameplay without delay. What’s more, Full HD 3D compatibility lets you enjoy 3D movies and games, while an internal speaker delivers room-filling sound for an immersive audiovisual experience.

Specifications

More Information

UPC	766907993318
Light Source	DLP Lamp
Display Resolution	Full HD (1920x1080)
Display Resolution	1920 x 1080
Brightness (Lumens)	3,000 ANSI
Screen Size	60 - 120 in. / 1.5 - 3.0 m
Throw Distance	3.0 - 7.2 ft / 0.9 - 2.2 m
Throw Ratio	0.69-0.83
Keystone	Vertical digital keystone correction (± 20º)
Lens	1.2x optical zoom
Light Source (watt)	240
Light Source Life, Normal (hours)	4000
Light Source Life, Dynamic Eco-Mode (hours)	15000
Color Depth	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio	22,000:1
Aspect Ratio	16:9
Input Lag	37ms
Frequency Horizontal	15K~102KHz
Frequency Vertical	23~120Hz
PC Resolution (max)	1920 x 1080
PC Resolution (min)	640 x 480
Mac® Resolution (max)	1920 x 1080
Mac® Resolution (min)	640 x 480
USB 3.1 Type C	1
3.5mm Audio Out	1
3.5mm Audio In	1
Control (RS232)	1
HDMI 1.4 In	2
VGA In	1
Composite RCA Video In	1
Mini USB	1
Internal Speakers	5W (x1)
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	310W
Stand-by	<0.5W

Physical Controls	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	0-90%
Kensington Lock Slot	1
Net (lbs)	6.0
Gross (lbs)	8.4
Net (kg)	2.7
Gross (kg)	3.8
Packaging (in.)	14.4 x 7.4 x 11.8
Physical (in.)	11.5 x 4.5 x 8.7
Packaging (mm)	365.0 188.0 x 300.0
Physical (mm)	293.0 x 115.0 x 220.0
Regulations	FCC, cTUVus, ROHS
Package Contents	PX706HD projector, power cable, USB Type C cable, remote control, Quick Start Guide
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907993318







Contact Sales
ViewSonic.com
888.881.8781
email:
salesinfo@viewsonic.com