


LS751HD - 5,000 ANSI LUMENS 1080P LASER BUSINESS/EDUCATION PROJECTOR


Key Features



30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



VGA(640 x 480) to 4K UHD (3840 x 2160)
RESOLUTION



x2 HDMI 1.4
x1 USB 2.0 Type-A
x1 Ethernet LAN (RJ45)
x1 3.5mm Audio Out
x1 RS232 In



1.6x Optical Zoom
Up To 30,000 Hours Lamp Life

FLEXIBLE CONNECTIVITY
for your favorite devices

Product Description

Experience better brightness on a smaller budget with the ViewSonic® LS751HD laser projector. This state-of-the-art projector delivers a stunning 5,000 ANSI lumens for crystal clear images even in bright rooms. Experience stunning 300" images with breathtaking colors for boardrooms, lecture halls and other public spaces on a long-lasting, eco-friendly projection solution that's designed for 24/7 usage. Enjoy versatile installation options with vertical lens shift, 1.6x optical zoom, easy image adjustment and 360° projection. HDMI 2.0b connectivity ensures access to 4K content with HDR/HLG support.

Specifications

More Information

UPC

766907023046

Light Source	Laser
Display Resolution	Full HD (1920x1080)
Display Resolution	1920 x 1080
Brightness (Lumens)	5,000 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	0.93-14.88m (100"@3.10m)
Throw Ratio	1.3-1.56
Keystone	Vertical (± 30º) / Horizontal (± 30º)
Lens	1.6x optical zoom
Light Source Life, Normal (hours)	20000
Light Source Life, Dynamic Eco-Mode (hours)	30000
Color Depth	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio	3,000,000:1
Aspect Ratio	16:9
Input Lag	37ms
Frequency Horizontal	15K~102KHz
Frequency Vertical	23-120Hz
PC Resolution (max)	VGA(640 x 480) to 4K UHD (3840 x 2160)
Mac® Resolution (max)	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4K UHD
USB 2.0 Type A	1
Ethernet LAN (RJ45)	1
3.5mm Audio Out	1
Control (RS232)	1
HDMI 1.4 (with HDCP 1.4)	2
Internal Speakers	15W (x1)
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	245W
Stand-by	<0.5W
Physical Controls	Keypad, Power key
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104º F (0 - 40º C)
Kensington Lock Slot	1
Net (lbs)	9.9
Gross (lbs)	14.6
Net (kg)	4.5

Gross (kg)	6.6
Packaging (in.)	19.5 x 7.7 x 15.2
Physical (in.)	13.3 x 10.4 x 5.2
Packaging (mm)	496 x 195 x 387
Physical (mm)	337 x 265 x 131.5
Regulations	cTUVus
Package Contents	Projector, power cable, remote control, Quick Start Guide
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907023046



5000 LUMENS
and Full HD (1920x1080) Resolution

Contact Sales
ViewSonic.com

888.881.8781
email:
salesinfo@viewsonic.com