


## VP2771 - 27" COLORPRO™ 1440P SRGB IPS MONITOR WITH 60W USB C


## Key Features

---


- Seamless Viewing Experience
  - WQHD Resolution
  - Loaded with Connectivity
  - Ultimate Color Accuracy
  - Excellent Screen Uniformity
- 



27  
**DISPLAY**



IPS  
**PANEL**



2560 x 1440  
**RESOLUTION**



## Product Description

---

Engineered to deliver unmatched color accuracy crucial for professional applications, the ViewSonic® VP2771 WQHD monitor displays your work with the vivid and lifelike color it deserves. With a SuperClear® IPS panel and a sleek frameless design, the VP2771 provides a near-seamless viewing experience ideal for multi-monitor setups. For simple, single-cable daisy chaining of multiple monitors, the VP2771 is equipped with future-proof DisplayPort technology, in addition to HDMI and USB type C ports. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E

[Download the ColorPro brochure.](#)

## Specifications

---

### More Information

<b>UPC</b>	766907847710
<b>Screen Size</b>	27
<b>Viewable Area (in.)</b>	27
<b>Panel Type</b>	IPS
<b>Display Resolution</b>	2560 x 1440
<b>Display Resolution</b>	WQHD (2560x1440)
<b>Static Contrast Ratio</b>	1,000:1
<b>Dynamic Contrast Ratio</b>	20M:1

<b>Light Source</b>	LED
<b>Brightness</b>	350 cd/m <sup>2</sup>
<b>Aspect Ratio</b>	16:9
<b>Response Time (Typical GTG)</b>	14ms
<b>Response Time (GTG w/OD)</b>	7ms
<b>Viewing Angles</b>	178° horizontal, 178° vertical
<b>Backlight Life (Hours)</b>	30,000
<b>Panel Surface</b>	Anti-glare, hard-coating (3H)
<b>PC Resolution (max)</b>	2560 x 1440
<b>USB Type A</b>	3
<b>USB Type B</b>	1
<b>USB Type C</b>	1
<b>3.5mm Audio Out</b>	1
<b>HDMI 1.4 In</b>	1
<b>DisplayPort</b>	1
<b>DisplayPort Out</b>	1
<b>Mini DisplayPort</b>	1
<b>Eco Mode (Conserve)</b>	28.5
<b>Eco Mode (optimized)</b>	32.9
<b>Consumption (typical)</b>	39.6
<b>Consumption (max)</b>	146.0
<b>Voltage</b>	AC 100-240V (universal), 50-60Hz
<b>Stand-by</b>	0.3W
<b>Cable Organization</b>	No
<b>Kensington Lock Slot</b>	1
<b>Physical Controls</b>	1, 2, 3, 4, 5, Power
<b>On Screen Display</b>	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Humidity (non-condensing)</b>	20-90%
<b>VESA Compatible</b>	100 x 100 mm
<b>Frequency Horizontal</b>	Analog: 15 ~ 130KHz; Digital: 15 ~ 90KHz
<b>Frequency Vertical</b>	Analog: 24 ~ 120Hz; Digital: 24 ~ 120Hz
<b>Analog Sync</b>	CPU GIO for MHL / TMDs for HDMI 1.4 , PCI-E
<b>Height Adjust</b>	130 mm / 5.1 in
<b>Swivel</b>	120°

<b>Pivot (Right/Left)</b>	90° / 90°
<b>Tilt (Forward/Back)</b>	5° / 21°
<b>Regulations</b>	CB ,CE, WEEE, RoHS, ErP, REACH, UL, cUL, FCC-B, Mexico CoC, Energy Star
<b>Net (lbs)</b>	15
<b>Net Without Stand (lbs)</b>	9.6
<b>Gross (lbs)</b>	23
<b>Net (kg)</b>	6.8
<b>Net Without Stand (kg)</b>	4.3
<b>Gross (kg)</b>	10.6
<b>Packaging (in.)</b>	28.3 x 10.6 x 18.1
<b>Physical (in.)</b>	24.1 x 21.5 x 8.5
<b>Physical Without Stand (in.)</b>	24.1 x 14.3 x 2.1
<b>Packaging (mm)</b>	720 x 268 x 460
<b>Physical (mm)</b>	613 x 546 x 216
<b>Physical Without Stand (mm)</b>	612.4 x 362.7 x 52.0
<b>Package Contents</b>	LCD Display, AC/DC Adapter, Power Cable, Mini DP to DisplayPort Cable, USB3.0 Up Stream Cable, Quick Start Guide, ViewSonic Wizard CD-Rom
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.
<b>Classification</b>	Discontinued

UPC: 766907847710



## Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)