

VP2771 - 27" COLORPRO™ 1440P SRGB IPS MONITOR WITH 60W USB C

Key Features

- Seamless Viewing Experience
- WQHD Resolution
- Loaded with Connectivity
- Ultimate Color Accuracy
- Excellent Screen Uniformity



27"
DISPLAY



IPS
PANEL



2560 x 1440
RESOLUTION



Product Description

Engineered to deliver unmatched color accuracy crucial for professional applications, the ViewSonic® VP2771 WQHD monitor displays your work with the vivid and lifelike color it deserves. With a SuperClear® IPS panel and a sleek frameless design, the VP2771 provides a near-seamless viewing experience ideal for multi-monitor setups. For simple, single-cable daisy chaining of multiple monitors, the VP2771 is equipped with future-proof DisplayPort technology, in addition to HDMI and USB type C ports. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E

[Download the ColorPro brochure.](#)

Specifications

	More Information
UPC	766907847710
Screen Size	27"
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	WQHD (2560x1440)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	20M:1
Light Source	LED
Brightness	350 cd/m2
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	7ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, hard-coating (3H)
PC Resolution (max)	2560 x 1440
USB Type A	3
USB Type B	1
USB Type C	1
3.5mm Audio Out	1
HDMI 1.4 In	1
DisplayPort	1
DisplayPort Out	1
Mini DisplayPort	1
Eco Mode (Conserve)	28.5
Eco Mode (optimized)	32.9
Consumption (typical)	39.6
Consumption (max)	146.0
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.3W
Cable Organization	No
Kensington Lock Slot	1

Physical Controls	1, 2, 3, 4, 5, Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	Analog: 15 ~ 130KHz; Digital: 15 ~ 90KHz
Frequency Vertical	Analog: 24 ~ 120Hz; Digital: 24 ~ 120Hz
Analog Sync	CPU GIO for MHL / TMD5 for HDMI 1.4 , PCI-E
Height Adjust	130 mm / 5.1 in
Swivel	120°
Pivot (Right/Left)	90° / 90°
Tilt (Forward/Back)	5° / 21°
Regulations	CB ,CE, WEEE, RoHS, ErP, REACH, UL, cUL, FCC-B, Mexico CoC, Energy Star
Net (lbs)	15
Net Without Stand (lbs)	9.6
Gross (lbs)	23
Net (kg)	6.8
Net Without Stand (kg)	4.3
Gross (kg)	10.6
Packaging (in.)	28.3 x 10.6 x 18.1
Physical (in.)	24.1 x 21.5 x 8.5
Physical Without Stand (in.)	24.1 x 14.3 x 2.1
Packaging (mm)	720 x 268 x 460
Physical (mm)	613 x 546 x 216
Physical Without Stand (mm)	612.4 x 362.7 x 52.0
Package Contents	LCD Display, AC/DC Adapter, Power Cable, Mini DP to DisplayPort Cable, USB3.0 Up Stream Cable, Quick Start Guide, ViewSonic Wizard CD-Rom
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Classification	Discontinued

UPC: 766907847710



Contact Sales
ViewSonic.com
 888.881.8781
 email: salesinfo@viewsonic.com