



VP2468-S


Key Features



24
DISPLAY



IPS
PANEL



Up to 1920x1080 non-interlaced
RESOLUTION



Product Description

The ViewSonic® VP2468 is a 24" (23.8" viewable) Full HD monitor that delivers unmatched color accuracy crucial for professional applications. With an edge-to-edge SuperClear® IPS panel and one of the world's thinnest bezels, the VP2468 provides a sleek and frameless viewing experience ideal for multi-monitor setups. For simple, single-cable daisy chaining of multiple monitors, the VP2468 is equipped with future-proof DisplayPort technology, in addition to HDMI ports. What's more, with advanced ergonomic tilt, swivel, pivot, and height adjust features, this monitor provides a comfortable viewing experience and vivid images no matter your vantage point. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E<2 value for superior color accuracy. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. Add to that 6-axis color adjustment functionality, and this monitor provides the ultimate color processing capability for professional applications. Hardware calibration is available with the optional ViewSonic Colorbration Kit, which allows you to quickly and easily calibrate the monitor for photography, graphic design, content creation, and other color-critical applications.

Specifications

	More Information
UPC	766907887419
Screen Size	24
Viewable Area (in.)	23.8
Panel Type	IPS
Display Resolution	1920 x 1080
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	20M:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Response Time (Typical GTG)	14ms

Response Time (GTG w/OD)	7ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, hard-coating (3H)
PC Resolution (max)	Up to 1920x1080 non-interlaced
Mac® Resolution (max)	Up to 1920x1080
USB 3.0 Type A	4
USB 3.0 Type B	1
3.5mm Audio Out	1
HDMI 1.4 In	2
DisplayPort	1
DisplayPort Out	1
Mini DisplayPort	1
Power in	3-pin plug (CEE22)
Eco Mode (Conserve)	17W
Eco Mode (optimized)	19W
Consumption (typical)	22W
Voltage	AC 100-240V (universal), 50-60Hz
Cable Organization	No
Physical Controls	Power, 1, 2, 3, 4, 5
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15~90kHz
Frequency Vertical	24~75Hz
Analog Sync	Separate Sync
Height Adjust	130 mm / 5.1 in
Swivel	120°
Pivot (Right/Left)	90° / 90°
Tilt (Forward/Back)	5° / 21°
Regulations	CB, CE, WEEE, RoHS, ErP, REACH, UL, FCC-B, Mexico CoC, EPEAT, ENERGY STAR, Mexico Energy
Net (lbs)	12.5
Net Without Stand (lbs)	7.0
Gross (lbs)	17.1

Net (kg)	5.7
Net Without Stand (kg)	3.2
Gross (kg)	7.75
Packaging (in.)	25.6 x 16.2 x 10.6
Physical (in.)	21.2 x 20.5 x 8.5
Physical Without Stand (in.)	21.2 x 12.2 x 1.9
Packaging (mm)	650 x 412 x 270
Physical (mm)	538.7 x 519.5 x 215
Physical Without Stand (mm)	538.7 x 310.5 x 48.1
Package Contents	VP2468 monitor, Power cable, Mini DisplayPort to DisplayPort cable, USB 3.0 Cable, Quick Start Guide, ViewSonic Wizard CD
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
Classification	Refurbished

UPC: 766907887419



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com