


VA2246MH-LED - 22" 1080P LED MONITOR WITH HDMI AND VGA AND ENHANCED VIEWING COMFORT

Key Features

- Full HD 1080p Resolution
- Enhanced Viewing Comfort
- The Power of HDMI
- Dual Integrated Speakers











What's in the box.



Product **Description**

The ViewSonic® VA2246mh-LED is a 22" (21.5" viewable) widescreen monitor with an LED backlight and a glossy, thin-bezel design ideal for use in the home or at the office. With Full HD 1920x1080 resolution and a 50M:1 MEGA Dynamic Contrast Ratio, the VA2246mh-LED delivers stunning brightness and contrast, while a quick 5ms response time ensures crisp pictures and smooth playback. As a complete multimedia package, the display also includes a pair of integrated speakers. VGA and HDMI inputs provide flexible and convenient connectivity, while a VESA-compatible mount offers additional flexibility. With a LED backlight and energy-saving Eco-mode, the VA2246mh-LED is an environmentally friendly display choice. In addition, a 3-year limited warranty, along with one of the industry's best pixel performance policies, make the VA2246mh-LED a great value choice for corporate and educational use as well.

Specifications

More Information	
UPC	766907911671
Screen Size	22
Viewable Area (in.)	21.5
Panel Type	TN
Display Resolution	1920 x 1080
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Color Space Support	(6-Bit+HI-FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	170º horizontal, 160º vertical
Backlight Life (Hours)	40,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	1920 x 1080
Mac® Resolution (max)	1920 x 1080
3.5mm Audio In	1
3.5mm Audio Out	1
VGA	1
HDMI 1.4 In	1
Internal Speakers	2.5W (x2)
Eco Mode (Conserve)	12W
Eco Mode (optimized)	16W
Consumption (typical)	22W
Consumption (max)	26W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1, 2, 3, 4, Power

On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	24 ~ 82KHz
Frequency Vertical	50 ~ 75Hz
Analog Sync	Separate Sync
Digital Sync	TMDS
Tilt (Forward/Back)	5° / 23°
Net (lbs)	7.7
Net Without Stand (lbs)	6.9
Gross (lbs)	10.3
Net (kg)	3.5
Net Without Stand (kg)	3.1
Gross (kg)	4.7
Packaging (in.)	22.2 x 15.4 x 4.5
Physical (in.)	20.1 × 14.4 × 7.8
Physical Without Stand (in.)	20.1 x 12.5 x 1.9
Packaging (mm)	565 x 391 x 114
Physical (mm)	509.6 x 366.1 x 197.6
Physical Without Stand (mm)	509.6 x 316.6 x 48.3
Regulations	cULus, FCC-B, ICES003, Energy Star 7.0, EPEAT Certified, UL-MX-CoC, Mexico Energy, CE EMC, CB, WEEE, RoHS, REACH SVHC List, ErP, EAC, UkrSEPRO
Package Contents	LCD Display, Power Cable, HDMI to HDMI (1.5m), Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907911671







Contact Sales
ViewSonic.com
888.881.8781 email:
salesinfo@viewsonic.com