



PA503S - 3800 LUMENS SVGA HOME WITH HDMI AND VERTICAL KEYSTONE

Key Features


- High brightness 3800 Lumens SVGA projector with advanced visual features
- 1.1x optical zoom, 40 degree vertical keystone for flexible setup
- A low 16ms input latency provides faster frame-by-frame action for smooth images without delay
- SuperEco Mode allows the lamp to shine bright for up to 15,000 hours
- Supports most media players, PCs, Macs, and mobile devices with inputs such as HDMI, VGA, mini USB



30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



VGA (640 x 480) to WUXGA_RB (1920 x 1200)
RESOLUTION

Flexible connectivity for your favorite devices.



1.1x optical zoom lens
15,000 hours lamp life (SuperEco Mode)



1x HDMI 1.4
2x VGA
1x RS232
1x Video In
1x Audio In/Out
1x Monitor Out
1x USB mini Type B

Product Description

The ViewSonic® PA503S price-performance projector features 3,800 lumens, native SVGA 800 x 600 resolution, and intuitive, user-friendly design. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. The PA503S also features extensive connectivity including HDMI, 2 x VGA, VGA out, Composite Video and audio in/out. An energy-saving SuperEco™ feature reduces power consumption and extends the lamp life by up to 15,000 hours. With advanced audio-visual features, flexible connectivity options, and an affordable price, the PA503S is ideal for use in education and small business environments.


*Energy consumption and lamp life may vary based on actual usage and other factors.

Specifications

UPC	766907904710
Light Source	DLP Lamp
Display Resolution	SVGA (800x600)
Display Resolution	800 x 600
Brightness (Lumens)	3,800 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	3.9 - 43 ft / 1.19 - 13.11 m
Throw Ratio	1.96 ~ 2.15
Keystone	Vertical (+/- 40°)
Lens	1.1x optical zoom
Light Source (watt)	190
Light Source Life, Normal (hours)	5000
Light Source Life, Dynamic Eco-Mode (hours)	15000
Color Depth	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio	22,000:1
Aspect Ratio	4:3
Input Lag	37ms
Frequency Horizontal	15K~102KHz
Frequency Vertical	23~120Hz
PC Resolution (max)	VGA (640 x 480) to WUXGA_RB (1920 x 1200)
Mac® Resolution (max)	VGA (640 x 480) to WUXGA_RB (1920 x 1200)
Mini USB Type B	1
3.5mm Audio Out	1
3.5mm Audio In	1
Control (RS232)	1
HDMI 1.4 In	1
VGA In	2
VGA Out	1
Composite RCA Video In	1
Internal Speakers	2W (x1)
Voltage	AC 100-240V (universal), 50-60Hz
Consumption (typical)	260W
Stand-by	<0.5W
Temperature	32-104° F (0 - 40° C)
Net (lbs)	4.9
Gross (lbs)	7.1

Net (kg)	2.2
Gross (kg)	3.2
Packaging (in.)	14.4 x 7.4 x 11.8
Physical (in.)	11.6 x 4.3 x 8.6
Packaging (mm)	365 x 188 x 300
Physical (mm)	294 x 110 x 218
Regulations	FCC (including ICES-003), cTUVus
Package Contents	PA503S projector, power cable, VGA cable, remote control, Quick Start Guide
Warranty	Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907904710



Contact Sales
ViewSonic.com
 888.881.8781
 email:
salesinfo@viewsonic.com