



VP2785-4K - 27" 4K UHD ADOBERGB COLORPRO™ IPS MONITOR W/ USB C & HDR10

Key Features


- Stunning 4K Ultra HD Resolution
- High Dynamic Range
- Loaded with Connectivity
- Ultimate Color Accuracy
- Excellent Screen Uniformity
- Seamless Viewing Experience



27
DISPLAY



IPS
PANEL



3840 x 2160
RESOLUTION



Product Description


- **PREMIUM MONITOR:** 4K UHD (3840x2160p) advanced ergonomic, 60Hz IPS monitor deliver lifelike colors perfect for office, graphic design, photographers and more
- **FRAMELESS DIGITAL CANVAS:** A three-sided ultra-thin bezel shows off more of your masterpiece, and less of the monitor
- **REDUCE CABLE CLUTTER:** Connect video, audio, data and power with a single USB-C cable and plug in peripherals like USB drives and mice with the USB hub
- **COLOR ACCURACY:** Screen wide 99% Adobe RGB, EBU, SMPTE-C, Rec. 709, and DICOM-SIM color spaces, Delta E<2 accuracy, and a smooth palette of 4.39 trillion colors deliver precise, lifelike images
- **HARDWARE CALIBRATION:** Quick and easy calibration ensures that the color displayed perfectly matches the original file
- **HDR10 CONTENT SUPPORT:** Displays videos as they are intended to be seen - giving you a fuller, more immersive viewing experience
- **FLEXIBLE CONNECTIVITY:** The VP2785-4K supports laptops, PCs, and Apple/Mac operating systems with USB 3.1 Type C, HDMI 2.0 with HDCP 2.2, DisplayPort, and Mini DisplayPort inputs
- **INCLUDED IN THE BOX:** LCD Monitor, Power Cable, AC/DC Adapter, USB 3.1 Type C Cable, Mini DP to DP Cable, USB 3.0 Cable, and Factory Color Calibration Report

Specifications

	More Information
UPC	766907902112
Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	3840 x 2160
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	20M:1
Light Source	LED
Brightness	350 cd/m2
Colors	1.07B
Color Space Support	10bit (8bit + A-FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	7ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	3840 x 2160
Mac® Resolution (max)	3840 x 2160
USB Type A	3
USB Type B	1
USB Type C	1
3.5mm Audio Out	1
HDMI 2.0 (with HDCP 2.2)	2
DisplayPort	1
Mini DisplayPort	1
Eco Mode (Conserve)	45
Eco Mode (optimized)	55
Consumption (typical)	67
Consumption (max)	70
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Cable Organization	No

Kensington Lock Slot	1
Physical Controls	1, 2, 3, 4, 5, Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~90KHz
Frequency Vertical	24 ~120Hz
Digital Sync	TMDS, PCI-E
Height Adjust	130 mm / 5.1 in
Swivel	120°
Pivot (Right/Left)	90° / 90°
Tilt (Forward/Back)	5° / 21°
Net (lbs)	14.1
Net Without Stand (lbs)	8.7
Gross (lbs)	22.3
Net (kg)	6.4
Net Without Stand (kg)	3.9
Gross (kg)	10.1
Packaging (in.)	28.3 x 10.6 x 18.1
Physical (in.)	24.1 x 21.5 x 8.5
Physical Without Stand (in.)	24.1 x 14.3 x 2.3
Packaging (mm)	720 x 268 x 460
Physical (mm)	612.4 x 545.5 x 215.0
Physical Without Stand (mm)	612.4 x 362.7 x 57.6
Regulations	UL, cUL, FCC-B, Mexico CoC, CB , CE, WEEE, RoHS, ErP, REACH, TCO6.0, Ukraine, GS, Ergo
Package Contents	VP2785-4K Display, AC/DC Adapter, Power Cable, Mini DP to DisplayPort Cable , USB 3.1 Gen 1 Type-C Cable, USB 3.0 Up Stream Cable, Quick Start Guide, ViewSoinc Wizard CD-Rom
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907902112



Contact Sales
[ViewSonic.com](https://www.viewsonic.com)
888.881.8781
email:
salesinfo@viewsonic.com