
PG800HD - BRIGHT 5000 LUMENS 1080P NETWORKABLE PROJECTOR WITH LENS SHIFT


Key **Features**

- 5,000 Lumen Brightness
- Vertical Lens Shift with Centered Lens
- Portall®: Discreet Wireless Streaming
- Network Monitoring & Control
- SuperColor™: Amazing Color Accuracy






30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



1920 x 1200
RESOLUTION



Product **Description**

Delivering 1920 x 1080 resolution and 5000 lumens of brightness, the ViewSonic® PG800HD is the ideal 1080p projector for professional installations, large venues, and business and education environments. With its 1.3x optical zoom, centered lens, vertical lens shift, and vertical keystoning, the PG800HD provides extreme flexibility even in the most challenging installations. The PG800HD boasts a sleek top cover design for quick lamp and accessory access, while an intuitive PortAll® compartment accommodates additional accessories such as an HDBaseT receiver, wireless streaming device, or PC stick. A 4-in-1 power button serves as a central point for LED notifications. Moreover, two HDMI ports and additional audio and video ports allow for extensive connectivity to handle multiple devices without the need to switch cables. Powered by SuperColor™ technology for beautiful image reproduction, and SonicExpert® technology for incredibly clear sound, the PG800HD delivers a professional audiovisual performance.

Specifications

More Information

UPC	766907934113
Light Source	DLP Lamp
Display Resolution	Full HD (1920x1080)
Display Resolution	1920 x 1080
Brightness (Lumens)	5,000 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	2.5 - 32.7 ft / .76 - 10 m
Throw Ratio	1.15-1.5
Keystone	Vertical (+/- 40°)
Lens	1.3x Manual optical zoom / manual optical focus
Light Source (watt)	370
Light Source Life, Normal (hours)	2000
Light Source Life, Dynamic Eco-Mode (hours)	2500
Color Depth	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio	5,000:1
Aspect Ratio	16:9
Input Lag	37ms
Frequency Horizontal	15K~102KHz
Frequency Vertical	23~120Hz
PC Resolution (max)	1920 x 1200
Mac® Resolution (max)	1920 x 1200
USB 2.0 Type A	1
USB 2.0 Type B	1
Ethernet LAN (RJ45)	1
3.5mm 12V Trigger	1
3.5mm Audio Out	1
3.5mm Audio In	2
Control (RS232)	1
HDMI In	2
VGA In	2
VGA Out	1
Composite RCA Video In	1
S-Video In	1
Mini USB	1
RCA Audio In (L/R)	1
3D VESA	1

IR out	1
Internal Speakers	10W (x2)
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (max)	574W
Stand-by	<0.5W
Physical Controls	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	0-90%
Kensington Lock Slot	1
Net (lbs)	13.7
Gross (lbs)	18.7
Net (kg)	6.2
Gross (kg)	8.5
Packaging (in.)	22.7 x 21.1 x 10.2
Physical (in.)	18.5 x 12.4 x 5.5
Packaging (mm)	577 x 537 x 260
Physical (mm)	470 x 316 x 140
AV Control	AMX Certified, ATEN Certified, Crestron Certified, Extron Certified, PJ Link Certified
Regulations	FCC, ROHS, cTUVus
Package Contents	PG800HD projector, power cable, VGA cable, remote control with AAA batteries, Quick Start Guide
Warranty	Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907934113







Contact Sales
ViewSonic.com
888.881.8781
email:
salesinfo@viewsonic.com