



VA2446MH-LED-S


Key Features



24"
DISPLAY



MVA
PANEL



1920 x 1080
RESOLUTION



Product Description

The ViewSonic® VA2446mh-LED is a 24" (23.6" viewable) widescreen monitor with a LED backlight and a glossy, thin-bezel design ideal for use in the home or at the office. With Full HD 1920x1080 resolution and a 50M:1 MEGA Dynamic Contrast Ratio, the VA2446mh-LED delivers stunning brightness and contrast, while a quick 5ms response time ensures crisp pictures and smooth playback. As a complete multimedia package, the display also includes a pair of integrated speakers. VGA and HDMI inputs provide flexible and convenient connectivity, while a VESA-compatible mount offers additional flexibility. With an efficient LED backlight and energy-saving Eco-mode, the VA2446mh-LED is an environmentally friendly display choice. In addition, a 3-year limited warranty, along with one of the industry's best pixel performance policies provides great value for the stylish, high-performance VA2446mh-LED display.

Specifications

More Information

UPC	766907952315
Screen Size	24"
Viewable Area (in.)	23.6
Panel Type	MVA
Display Resolution	1920 x 1080
Static Contrast Ratio	3,000:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	LED
Brightness	300 cd/m ²
Colors	16.7M
Color Space Support	(6-Bit+HI-FRC)
Aspect Ratio	16:9

Response Time (Typical GTG)	5ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	40,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	1920 x 1080
Mac® Resolution (max)	1920 x 1080
3.5mm Audio In	1
3.5mm Audio Out	1
VGA	1
HDMI 1.4 In	1
Internal Speakers	2.5W (x2)
Eco Mode (Conserve)	17W
Eco Mode (optimized)	21W
Consumption (typical)	26W
Consumption (max)	28W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1, 2, 3, 4, Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	24 ~ 82KHz
Frequency Vertical	50 ~ 75Hz
Digital Sync	TMDS
Tilt (Forward/Back)	5° / 22°
Regulations	cULus, FCC-B, ICES003, Energy Star, EPEAT, Mexico Energy, MX-CoC, CE, REACH, WEEE, eAC, UkrSEPRO
Net (lbs)	9.02
Net Without Stand (lbs)	8.1
Gross (lbs)	12.0
Net (kg)	4.1
Net Without Stand (kg)	3.7
Gross (kg)	5.4

Packaging (in.)	24.6 x 16.9 x 4.7
Physical (in.)	22.3 x 15.7 x 8.3
Physical Without Stand (in.)	22.3 x 13.6 x 1.9
Packaging (mm)	624.0 x 429.0 x 118.0
Physical (mm)	566.4 x 397.4 x 211.2
Physical Without Stand (mm)	566.4 x 346.3 x 48.0
Package Contents	LCD Display, Power Cable , VGA Cable , Audio Cable , Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
Classification	Refurbished

UPC: 766907952315



Contact Sales
ViewSonic.com

888.881.8781 
 email: salesinfo@viewsonic.com 