CDX5562

Key **Features**

- Ultra-narrow Bezel
- SuperClear® IPS Panel Technology
- 10x10 Tiling Support with DisplayPort or DVI
- Control Multiple Devices
- Free Bundled vController™ Software



55"
DISPLAY

PANEL

RESOLUTION



Product **Description**

The ViewSonic® CDX5562 is a 55" (54.64'' viewable) commercial display with a super ultra-narrow bezel optimized for multi-panel video wall applications. With an edge-to-edge bezel width of only 1.8mm between combined displays, and 10x10 installation via DisplayPort or DVI daisy-chain, the CDX5562 delivers nearly seamless, high-impact video walls for public, retail, and transportation settings. With Full HD 1080p resolution, 700-nit high brightness, SuperClear® technology for wide viewing angles, and dual 10W stereo speakers, the CDX5562 delivers sharp, vivid images with incredible sound and multimedia performance.

Specifications


More Information


UPC	766907961614
CPU	USB Supported internal media player

Built-in Software	OSD / Remote Control
Internal Speakers	10W (x2)
HDMI 1.4 In	2
DVI-D	1
DVI-D Out	1
VGA	1
DisplayPort	1
DisplayPort Out	1
Composite RCA	1
Component RCA	1
3.5mm Audio In	1
3.5mm Audio Out	1
Speaker Out	1
USB 2.0	1
Slot-in PC Slot	1
RS232	1
RS232 Out	1
Ethernet LAN (RJ45)	1
Voltage	100-240 VAC
Consumption With Slot-In PC (typical)	334W
Consumption Without Slot-In PC (typical)	270W
Stand-by	<0.5W
Temperature	41-104º F (5 - 40º C)
Humidity (non-condensing)	20-80%
Net (lbs)	58.8
Net Without Stand (lbs)	53.7
Gross (lbs)	81.1
Net (kg)	26.7
Net Without Stand (kg)	24.4
Gross (kg)	36.8
Packaging (in.)	58.1 x 38.7 x 14.8
Physical (in.)	47.7 x 26.9 x 3.9
Packaging (mm)	1475.0 x 983.0 x 375.0
Physical (mm)	1211.4 x 682.2 x 98.5
VESA Compatible	400 x 400 mm
Screw Size	M6

Screw Length (mm)	10
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Package Contents	CDX5562 Commercial Display, Remote control, User Manual, Quick Start Guide, power cables, VGA cable, RS232 cable, IR sensor cable, RS232 daisy chain cable, Edge Alignment kit 1 & 2, Thumb screw
Regulations	UL/cUL, FCC, Energy Star 6.0, UL-MX-CoC, Mexico Energy
Classification	Discontinued
Screen Size	55"
Viewable Area (in.)	54.6
Orientation	Landscape / Portrait
Light Source	DLED
Display Resolution	1920 x 1080
Aspect Ratio	16:9
Static Contrast Ratio	1,200:1
Backlight Life (Hours)	50,000
Brightness	700 cd/m2
Response Time (Typical GTG)	8ms
Bezel Width (in.)	Top 0.035 in / Left 0.035 in / Bottom 0.035 in / Right 0.035 in
Bezel Width (mm)	Top 0.9 mm / Left 0.9 mm / Bottom 0.9 mm / Right 0.9 mm
Viewing Angles	178º horizontal, 178º vertical
Panel Surface	Anti-glare, Hard coating (3H)
Operation Rating	24/7

UPC: 766907961614







Contact Sales

ViewSonic.com
888.881.8781
email:
salesinfo@viewsonic.com