



TD1711 - 17" DISPLAY, TN PANEL, 1280 X 1024 RESOLUTION

Key Features


- Resistive Touch Technology
- MEGA Dynamic Contrast Ratio
- Control Multiple Devices
- Ergonomic Design



17"
DISPLAY



TN
PANEL



1280 x 1024
RESOLUTION



Product Description

The TD1711 is a 17" 5:4 aspect ratio monitor with resistive touch technology. With a robust, pressure-sensing touchscreen that is resistant to screen contamination, the TD1711 is ideal for use in retail, POS, and commercial environments. Resistive touch technology on the TD1711 is also fully functional in gloved environments and compatible with styluses. Featuring 20M:1 MEGA Dynamic Contrast Ratio, the TD1711 delivers extremely sharp and crisp images. Flexible connectivity options include VGA, HDMI with CEC, RS232, and USB ports. A VESA-mountable design offers additional convenience for use as a wall-mounted display. Industry-leading warranty protection and ViewSonic product quality makes this durable touch display a great long-term investment for a variety of environments.

Specifications

More Information

UPC

766907979817

Screen Size

17"

Viewable Area (in.)	17
Panel Type	TN
Display Resolution	1280 x 1024
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	20,000,000:1
Light Source	WLED
Brightness	250 cd/m2
Colors	16.7M
Color Space Support	6 bits + Hi FRC
Aspect Ratio	5:4
Response Time (Typical GTG)	5ms
Viewing Angles	170° horizontal, 160° vertical
Backlight Life (Hours)	30,000
Panel Surface	Hard coating (3H), Haze 8% or below
Refresh Rate	60Hz
PC Resolution (max)	1280 x 1024
USB Type A	2
USB Type B	1
3.5mm Audio In	1
3.5mm Audio Out	1
VGA	1
HDMI 1.4 (with CEC)	1
RS232 In	1
Touch Technology	Resistive
Touch Points	1-Point Touch
Internal Speakers	1W (x2)
Eco Mode (Conserve)	10.1W
Eco Mode (optimized)	11.4W
Consumption (typical)	12.6W
Consumption (max)	17W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.3W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1, 2, 3, 4, Power

On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	24 ~ 82KHz
Frequency Vertical	50 ~ 75Hz
Digital Sync	TMDS
Tilt (Forward/Back)	5° / 90°
Regulations	cTUVus, FCC-B, ICES003, Energy Star 7.1, EPEAT, TUV Mexico CoC, Mexico Energy
Net (lbs)	8.6
Net Without Stand (lbs)	6.0
Gross (lbs)	11.7
Net (kg)	3.9
Net Without Stand (kg)	2.7
Gross (kg)	5.3
Packaging (in.)	17.7 x 16.3 x 6.8
Physical (in.)	14.5 x 13.7 x 8.2
Physical Without Stand (in.)	14.5 x 12.4 x 1.9
Packaging (mm)	450.0 x 415.0 x 172.0
Physical (mm)	368.7 x 347.6 x 208.0
Physical Without Stand (mm)	368.7 x 314.4 x 46.9
Package Contents	TD1711 Display, Power Cable, VGA Cable, USB Cable, Audio Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
UPC: 766907979817	



Contact Sales

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com