LS900WU - 6000 LUMENS WUXGA NETWORKABLE LASER PROJECTOR WITH HV KEYSTONE AND LENS SHIFT

Key **Features**

- Bright Images in any Environment
- Long-lasting Laser Phosphor Light Source
- One-Wire HDBT® Input
- 360-Degree Orientation
- Portrait Mode Projection
- Software Updates Via Mini USB
- Peace of Mind



50 - 300 in. / 1.27 - 7.62 m
DISPLAY



PANEL



1920 x 1200
RESOLUTION



Product **Description**

Bright and versatile for any professional installation, the ViewSonic® LS900WU WUXGA laser projector delivers everything you need for big screens in big venues. Delivering 6,000 lumens of advanced high brightness, 100,000:1 contrast ratio, and up to 30,000 hours* of light source life, this projector is ideal for auditoriums, lecture halls, large boardrooms, houses of worship, and more. Thanks to SuperColor™ technology, content is brought to life with captivating color, crisp graphics, and stunning videos no matter the environment. This top-notch performer is also easy to deploy and manage with its wide 1.65x optical zoom adjustment, vertical/horizontal keystone, 4 corner adjustment, and a vertical/horizontal lens shift feature that provide extreme flexibility in even the most challenging installations. Thanks to the built-in HDBT receiver, the projector is capable of receiving uncompressed HD video and audio from over 200 feet away via network cable. Moreover, 360-degree tilt angle projection, portrait mode, and 24/7 operation allow for extreme mounting flexibility. The ViewSonic® LS900WU is the ideal WUXGA laser projector for professional installations, large venues, and business and education environments. *Light source life may vary based on actual usage and other factors.

Specifications

More Information	
UPC	766907001242
Light Source	DLP Laser
Display Resolution	WUXGA (1920x1200)
Display Resolution	1920 x 1200
Brightness (Lumens)	6,000 ANSI
Screen Size	50 - 300 in. / 1.27 - 7.62 m
Throw Distance	4.0 - 24.4 ft / 1.24 - 7.43 m
Throw Ratio	1.2 - 1.9
Keystone	Vertical (+/- 25º) / Horizontal (+/- 30º)
Lens	1.65x optical zoom
Light Source (watt)	Laser bank x 4
Light Source Life, Normal (hours)	20000
Light Source Life, Dynamic Eco-Mode (hours)	30000
Color Depth	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio	100,000:1
Aspect Ratio	16:10
Input Lag	37ms
Lens Shift	Horizontal (-2.5% +2.5%) / Vertical (-2.4% +9.2%)
Frequency Horizontal	15K~102KHz
Frequency Vertical	23~120Hz
PC Resolution (max)	1920 x 1200
PC Resolution (min)	640 x 480
Mac® Resolution (max)	1920 x 1200
Mac® Resolution (min)	640 x 480
USB 2.0 Type A	1
Ethernet LAN (RJ45)	1
3.5mm Audio Out	1
3.5mm Audio In	1
Control (RS232)	1
HDMI In	3
VGA In	1
VGA Out	1
Composite RCA Video In	1

Mini USB	1
RCA Audio In (L/R)	1
RCA Audio Out	1
3D VESA	1
HDBT	1
Internal Speakers	5W (x2)
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	430W
Stand-by	<0.5W
Physical Controls	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	0-90%
Kensington Lock Slot	1
Net (lbs)	24.2
Gross (lbs)	30.0
Net (kg)	11.0
Gross (kg)	13.6
Packaging (in.)	22.0 x 11.9 x 18.5
Physical (in.)	14.2 x 6.3 x 17.3
Packaging (mm)	559.0 x 301.0 x 469.0
Physical (mm)	360.0 x 161.0 x 440.0
Regulations	FCC, UL/CUL, ROHS
Package Contents	LS900WU projector, power cable, VGA cable, remote control, Quick Start Guide
Warranty	Five-year limited warranty on parts and labor, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907001242



Contact Sales
ViewSonic.com
888.881.8781
email:
salesinfo@viewsonic.com