




VX2776-4K-MHD - 27" 4K UHD THIN-BEZEL IPS MONITOR WITH HDMI AND DISPLAYPORT

Key Features


- 27 Inch 4K UHD (3840x2160p) IPS monitor with thin bezels and 60Hz refresh rate
- HDR10 content support for deep contrast, rich color, and vibrant details
- Optimized view settings offers "Game," "Movie," "Web," "Text," and "Mono" presets
- Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- The VX2776-4K-MHD supports laptops, PCs, and Macs with HDMI, and DisplayPort inputs




What's in the box.



**27
DISPLAY**



**IPS
PANEL**



**3840 x 2160
RESOLUTION**



*Power Cable varies by region




Product Description

Whether for office use or for enjoying entertainment at home, the ViewSonic® VX2776-4K-mhd is designed to take your viewing experience to another level. With a SuperClear® IPS panel and a sleek frameless design, this monitor provides a near-seamless viewing experience ideal for multi-monitor setups. Stunning 4K Ultra HD resolution delivers 4-times more pixels than Full HD monitors, which boosts efficiency and image detail needed for work or play. A mega dynamic contrast ratio of 80M:1 delivers enhanced image depth for a better user experience. Moreover, HDR10 content support delivers vivid colors and brightness that exceed standard monitors. Built-in HDMI and DisplayPort inputs deliver flexible connectivity options for a wide range of devices.

Specifications

	More Information
UPC	766907995817
Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	3840 x 2160
Display Resolution	4K (3840x2160)
Static Contrast Ratio	1,300:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	WLED
Brightness	350 cd/m2
Colors	1.07B
Color Space Support	8-bit+Hi-FRC
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	4ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	3840 x 2160
3.5mm Audio Out	1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	2.5W (x2)
Eco Mode (Conserve)	34W
Eco Mode (optimized)	39W
Consumption (typical)	44W
Consumption (max)	48W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1,2,3,4,Power

On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 160 KHz
Frequency Vertical	40 ~ 75 Hz
Digital Sync	TMDS for HDMI (v2.0), PCI-E for DisplayPort (v1.2)
Net (lbs)	12.3
Net Without Stand (lbs)	11.0
Gross (lbs)	15.4
Net (kg)	5.6
Net Without Stand (kg)	5.0
Gross (kg)	7.0
Packaging (in.)	27.4 x 18.2 x 5.2
Physical (in.)	24.3 x 17.8 x 7.2
Physical Without Stand (in.)	24.3 x 14.4 x 1.8
Packaging (mm)	697.0 x 462.0 x 132.0
Physical (mm)	616.0 x 451.0 x 184.0
Physical Without Stand (mm)	616.0 x 366.0 x 46.0
Regulations	MX-CoC, Mexico Energy, CE, CE EMC, CB, Energy Star compliant
Package Contents	VX2776-4K, Power Cable, HDMI Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
UPC: 766907995817	



Contact Sales
[ViewSonic.com](https://www.viewsonic.com)
 888.881.8781
 email: salesinfo@viewsonic.com