


VG3448 - 34" 1440P ERGONOMIC 21:9 MONITOR WITH FREESYNC, HDMI, DP, AND MINI DP

Key Features


- 34 Inch ultrawide 21:9 WQHD (2560x1440p) WLED monitor with 60Hz refresh rate
- Advanced ergonomics (40-degree tilt, swivel, and height) for all-day comfort
- Easy-to-install quick release stand with carrying handle and client mount
- Eco friendly easy-open box for streamlined monitor setup
- The VG3448 supports laptops, PCs, Macs and more with HDMI, USB, DisplayPort, mini DP inputs



34
DISPLAY



MVA
PANEL



3440x1440
RESOLUTION



Product Description

Featuring an ultra-wide 34" screen, the ViewSonic® VG3448 monitor is ideal for both office use and home entertainment. With WQHD 3440 x 1440 resolution, the VG3448 delivers 2.4 times more pixels than standard Full HD monitors, giving users more detail for work or play. A 21:9 aspect ratio and slim bezels provide extra screen real estate so users can display more content, switch between applications more quickly, view documents side by side, and view multiple windows at once. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for simple out-of-the box setup. The quick release stand also includes an integrated client mount and cable management features, making this monitor perfect for deployment in cloud-based environments.

Specifications

More Information	
UPC	766907002331
Screen Size	34
Panel Type	MVA
Display Resolution	3440 x 1440
Display Resolution	QHD (3440x1440)
Static Contrast Ratio	3,000:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	WLED
Brightness	300 cd/m2

Colors	1.07B
Color Space Support	10 bit (8 bit + FRC)
Aspect Ratio	21:9
Response Time (Typical GTG)	25ms
Response Time (GTG w/OD)	5ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
Adaptive Sync	AMD FreeSync™
PC Resolution (max)	3440x1440
Mac® Resolution (max)	3440x1440
USB Type A	4
USB 2.0 Type B	1
HDMI 1.4 In	2
DisplayPort	1
Mini DisplayPort	1
Internal Speakers	3W (x2)
Eco Mode (Conserve)	36W
Eco Mode (optimized)	38W
Consumption (typical)	41W
Consumption (max)	76W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1,2,3,4,5,Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 150 KHz
Frequency Vertical	24 ~ 100 Hz
Digital Sync	PCI-E
Height Adjust	130 mm / 5.1 in

Swivel	120°
Tilt (Forward/Back)	40° / 5°
Regulations	cTUVus, FCC-B, ICES003, Energy Star Certified, EPEAT Certified, MX-CoC, Mexico Energy
Net (lbs)	19.0
Net Without Stand (lbs)	13.2
Gross (lbs)	29.5
Net (kg)	8.6
Net Without Stand (kg)	6.0
Gross (kg)	29.5
Packaging (in.)	37.2 x 9.2 x 20.7
Physical (in.)	32.5 x 16.1 x 9.3
Physical Without Stand (in.)	32.5 x 14.4 x 2.0
Packaging (mm)	945.0 x 234.0 x 525.0
Physical (mm)	825.0 x 408.0 x 236.0
Physical Without Stand (mm)	825.0 x 366.0 x 51.0
Package Contents	VG3448 Display, Power Cable, Mini DP to DP Cable, USB 3.1 Upstream Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907002331



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com