


PS600W-S


Key Features

REFURBISHED


- SuperColor: Amazing Color Accuracy
 - Large Images In Small Spaces
 - 3,500 Lumen Brightness
 - Horizontal and Vertical Keystone
 - Long Lamp Life
 - Compatible with Interactive Whiteboard Module
-



30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



1920 x 1080
RESOLUTION



Product Description

The ViewSonic® PS600W networkable projector features 3,500 lumens, native WXGA 1280x800 resolution, and an intuitive, user-friendly design. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment, and a 10W speaker delivers incredibly clear and audible sound. A short throw lens with a 0.49 throw ratio offers large projection images for smaller rooms. With HV keystone, corner adjustment, and easy network management, the PS600W provides flexible setup. Designed with smarter features and extensive connectivity, the networkable short throw PS600W is ideal for use in education and corporate environments.

Specifications

	More Information
UPC	766907983814
Light Source	DLP Lamp
Display Resolution	WXGA (1280x800)
Display Resolution	1280 x 800
Brightness (Lumens)	3,500 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	2.1 - 6.2 ft / 0.6 - 1.9 m
Throw Ratio	0.5

Keystone	Vertical (+/- 40°) / Horizontal (+/- 26°)
Lens	Fixed Zoom
Light Source (watt)	200
Light Source Life, Normal (hours)	5000
Light Source Life, Dynamic Eco-Mode (hours)	15000
Color Depth	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio	22,000:1
Aspect Ratio	16:10
Input Lag	37ms
Frequency Horizontal	15K~102KHz
Frequency Vertical	23~120Hz
PC Resolution (max)	1920 x 1080
PC Resolution (min)	640 x 480
Mac® Resolution (max)	1920 x 1080
Mac® Resolution (min)	640 x 480
USB 2.0 Type A	1
Ethernet LAN (RJ45)	1
3.5mm Audio Out	1
3.5mm Audio In	1
Control (RS232)	1
HDMI 1.4 In	2
VGA In	2
VGA Out	1
Composite RCA Video In	1
Mini USB	1
Internal Speakers	10W (x1)
Voltage	100-240V +/- 10%, 50/60Hz AC
Consumption (typical)	260W
Stand-by	<0.5W
Physical Controls	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	0-90%
Kensington Lock Slot	1
Net (lbs)	5.7

Gross (lbs)	7.2
Net (kg)	2.6
Gross (kg)	3.3
Packaging (in.)	14.4 x 7.4 x 11.8
Physical (in.)	11.5 x 4.5 x 9.3
Packaging (mm)	365.0 188.0 x 300.0
Physical (mm)	292.0 x 115.0 x 236.0
AV Control	AMX Certified, ATEN Certified, Crestron Certified, PJ Link Certified
Regulations	FCC, cTUVus, ROHS
Package Contents	PS600W projector, power cable, VGA cable, remote control, Quick Start Guide
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Classification	Refurbished

UPC: 766907983814



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com