


VS2412-H

Key Features

REFURBISHED


- Full HD 1080p Resolution
- Enhanced Viewing Comfort
- The Power of HDMI
- Optimized View Settings
- Ergonomic Design



24"
DISPLAY



IPS
PANEL



1920 x 1080
RESOLUTION

Product Description

The ViewSonic® VS2412-h is a 24" (23.8" viewable) widescreen monitor with a LED backlight, and thin-bezel design ideal for use in the home or at the office. With Full HD 1920x1080 resolution and a 50M:1 MEGA Dynamic Contrast Ratio, the VS2412-h delivers stunning brightness and contrast, while a quick 5ms response time ensures crisp pictures and smooth playback. It also features full-ergonomic functionality, including tilt, swivel, pivot and height adjustments for maximum productivity and comfort. VGA and HDMI inputs provide flexible and convenient connectivity, while a VESA-compatible mount offers additional flexibility.

Specifications

More Information

UPC	766907005172
Screen Size	24"
Viewable Area (in.)	23.8
Panel Type	IPS

Display Resolution	1920 x 1080
Display Resolution	Full HD (1920x1080)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Color Space Support	6 bits with Hi-FRC color depth
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	5ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating 3H
PC Resolution (max)	1920 x 1080
Mac® Resolution (max)	1920 x 1080
3.5mm Audio Out	1
VGA	1
HDMI 1.4 In	1
Eco Mode (Conserve)	13W
Eco Mode (optimized)	18W
Consumption (typical)	20W
Consumption (max)	22W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key Buttons 1, 2, 3, 4, 5 (Power)
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	24 ~ 83 KHz
Frequency Vertical	50 ~ 75 Hz

Digital Sync	TMDS
Height Adjust	135 mm / 5.3 in
Pivot (Right/Left)	90° / 90°
Tilt (Forward/Back)	3° / 20°
Regulations	cTUVus, FCC-B, ICES003, CEC
Net (lbs)	10.4
Net Without Stand (lbs)	7.3
Gross (lbs)	14.1
Net (kg)	4.7
Net Without Stand (kg)	3.3
Gross (kg)	6.4
Packaging (in.)	23.8 x 17.5 x 7.8
Physical (in.)	21.7 x 17.0 x 9.4
Physical Without Stand (in.)	21.7 x 13.0 x 2.0
Packaging (mm)	605.0 x 445.0 x 198.0
Physical (mm)	551.0 x 431.2 x 240.0
Physical Without Stand (mm)	551.0 x 331.0 x 50.0
Package Contents	VS2412-h, Power Cable, VGA Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Classification	Discontinued

UPC: 766907005172



Contact Sales

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com