

VX2776-4K-MHD-S

## Key Features



27  
**DISPLAY**



IPS  
**PANEL**



3840 x 2160  
**RESOLUTION**



## Product Description

Whether for office use or for enjoying entertainment at home, the ViewSonic® VX2776-4K-mhd is designed to take your viewing experience to another level. With a SuperClear® IPS panel and a sleek frameless design, this monitor provides a near-seamless viewing experience ideal for multi-monitor setups. Stunning 4K Ultra HD resolution delivers 4-times more pixels than Full HD monitors, which boosts efficiency and image detail needed for work or play. A mega dynamic contrast ratio of 80M:1 delivers enhanced image depth for a better user experience. Moreover, HDR10 content support delivers vivid colors and brightness that exceed standard monitors. Built-in HDMI and DisplayPort inputs deliver flexible connectivity options for a wide range of devices.

## Specifications

### More Information

<b>UPC</b>	766907005073
<b>Screen Size</b>	27
<b>Viewable Area (in.)</b>	27
<b>Panel Type</b>	IPS
<b>Display Resolution</b>	3840 x 2160
<b>Display Resolution</b>	4K (3840x2160)
<b>Static Contrast Ratio</b>	1,300:1
<b>Dynamic Contrast Ratio</b>	80,000,000:1
<b>Light Source</b>	WLED
<b>Brightness</b>	350 cd/m2
<b>Colors</b>	1.07B
<b>Color Space Support</b>	8-bit+Hi-FRC
<b>Aspect Ratio</b>	16:9

<b>Response Time (Typical GTG)</b>	14ms
<b>Response Time (GTG w/OD)</b>	4ms
<b>Viewing Angles</b>	178° horizontal, 178° vertical
<b>Backlight Life (Hours)</b>	30,000
<b>Panel Surface</b>	Anti-glare, Hard coating (3H)
<b>PC Resolution (max)</b>	3840 x 2160
<b>3.5mm Audio Out</b>	1
<b>HDMI 2.0 In</b>	2
<b>DisplayPort</b>	1
<b>Internal Speakers</b>	2.5W (x2)
<b>Eco Mode (Conserve)</b>	34W
<b>Eco Mode (optimized)</b>	39W
<b>Consumption (typical)</b>	44W
<b>Consumption (max)</b>	48W
<b>Voltage</b>	AC 100-240V (universal), 50-60Hz
<b>Stand-by</b>	0.5W
<b>Cable Organization</b>	No
<b>Kensington Lock Slot</b>	1
<b>Physical Controls</b>	1,2,3,4,Power
<b>On Screen Display</b>	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Humidity (non-condensing)</b>	20-90%
<b>VESA Compatible</b>	100 x 100 mm
<b>Frequency Horizontal</b>	15 ~ 160 KHz
<b>Frequency Vertical</b>	40 ~ 75 Hz
<b>Digital Sync</b>	TMDS for HDMI (v2.0), PCI-E for DisplayPort (v1.2)
<b>Regulations</b>	MX-CoC, Mexico Energy, CE, CE EMC, CB, Energy Star compliant
<b>Net (lbs)</b>	12.3
<b>Net Without Stand (lbs)</b>	11.0
<b>Gross (lbs)</b>	15.4
<b>Net (kg)</b>	5.6
<b>Net Without Stand (kg)</b>	5.0
<b>Gross (kg)</b>	7.0
<b>Packaging (in.)</b>	27.4 x 18.2 x 5.2
<b>Physical (in.)</b>	24.3 x 17.8 x 7.2

<b>Physical Without Stand (in.)</b>	24.3 x 14.4 x 1.8
<b>Packaging (mm)</b>	697.0 x 462.0 x 132.0
<b>Physical (mm)</b>	616.0 x 451.0 x 184.0
<b>Physical Without Stand (mm)</b>	616.0 x 366.0 x 46.0
<b>Package Contents</b>	VX2776-4K, Power Cable, HDMI Cable, Quick Start Guide
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.
<b>Warranty</b>	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
<b>Classification</b>	Refurbished

UPC: 766907005073



### Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781 

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com) 