



PX701-4K - 4K UHD PROJECTOR WITH 3200 LUMENS, 240HZ, 4.2MS FOR HOME THEATER AND GAMING

Key Features


- Bright 3200 Lumens 4K UHD projector with high contrast ratio and advanced visual features
- Experience gaming on the big screen with 4.2ms low input lag and a magnificent 240Hz refresh rate
- With a 1.1x optical zoom, anti-warping stabilization and H/V keystone, you can project on flat and curved surfaces
- SuperColor technology and HDR/HGL support offers a wide color gamut
- SuperEco Mode allows the lamp to shine bright for up to 20,000 hours
- Supports most media players, gaming consoles, PCs, Macs, and mobile devices with inputs such as Dual HDMI, Powered USB A



30 - 300 in. / 0.76 - 7.62 m
DISPLAY




PANEL



3840 x 2160
RESOLUTION

Where to place your projector to get the screen size you want.



Projection Distance

*Based on throw ratio of 1.5-1.65

**Can project up to 762 m | 300 in.

*** Ceiling Mountable

Product Description



For an incredible entertainment experience from the comfort of home, the ViewSonic® PX701-4K projector delivers stunning Ultra HD resolution at an affordable price. While true 4K resolution and HDR support make this projector ideal for movie watching, users will enjoy its low 4.2ms input lag and 240Hz refresh rate for casual gaming. With 3200 lumens and room-filling sound, this projector provides bright visuals and immersive audio in nearly any room or environment. An automatic horizontal and vertical keystone feature, along with four-corner adjustment, delivers flexible setup of image sizes up to 300 inches.

Specifications

UPC	766907007893
Light Source	DLP Lamp
Display Resolution	4K (3840x2160)
Display Resolution	3840 x 2160
Brightness (Lumens)	3,200 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	1m~10.96m (100"@3.32m)
Throw Ratio	1.5-1.65
Keystone	Vertical (+/- 40°) / Horizontal (+/- 40°)
Lens	1.1x optical zoom
Light Source (watt)	203
Light Source Life, Normal (hours)	6000
Light Source Life, Dynamic Eco-Mode (hours)	20000
Color Depth	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio	12,000:1
Aspect Ratio	16:9
Input Lag	37ms
Frequency Horizontal	15K-129KHz
Frequency Vertical	23-240Hz
PC Resolution (max)	3840 x 2160
PC Resolution (min)	640 x 480
Mac® Resolution (max)	3840 x 2160
Mac® Resolution (min)	640 x 480
USB 2.0 Type A	1
3.5mm Audio Out	1
RS232 Out	1
HDMI 2.0 In	2
Internal Speakers	10W (x1)
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	290W
Stand-by	<0.5W
Physical Controls	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	0-90%

Kensington Lock Slot	1
Net (lbs)	6.2
Gross (lbs)	8.8
Net (kg)	2.8
Gross (kg)	4
Packaging (in.)	16.3 x 6.6 x 11.7
Physical (in.)	12.3 x 4.3 x 8.7
Packaging (mm)	415.0 x168.0 x 297.0
Physical (mm)	312.0 x 108.0 x 222.0
Regulations	FCC, cTUVus, ROHS
Package Contents	PX701-4K, power cable, remote control, Quick Start Guide
Warranty	Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907007893



Contact Sales
ViewSonic.com

888.881.8781
email:
salesinfo@viewsonic.com