

LD108-121 - 108" DISPLAY, 1920 X 1080 RESOLUTION, 500-NIT BRIGHTNESS, 24/7


Key Features

- All-in-One Solution
- Powerful Embedded SoC Platform
- Multi-Panel Modular Design for Easy Installation
- Vivid Colors and Stunning Images
- AV Control System Compatible











Product **Description**

The ViewSonic® LD108-121 is a premium all-in-one direct view LED commercial display. With a huge 108" screen size, the LD108-121 is built to impress as a centerpiece in any conference room, boardroom, or lobby. Along with its immense screen size, this display delivers stunning visuals with Full HD resolution, 1.25mm fine pixel pitch, 500-nit high brightness, 4,440Hz ultra-fast refresh rate, and 120% Rec.709 wide color gamut.

Integrated ViewBoard® Cast screen sharing software* (along with optional ViewSonic vCastSender app), enables both on-site and online attendees to participate in video conferences and simultaneously share content. Equipped with twin dual-core processors, 4GB RAM, and 32GB of internal memory, the LD108-121 can play multimedia from internal storage or a USB flash drive 24 hours a day, seven days a week. And with remote configuration and content management system support, the ViewSonic LD108-121 is also suitable for a wide array of diverse signage applications. *Chrome, Android, Windows, Mac OS, and iOS compliant

Specifications

	More Information
UPC	766907010459
os	Android 8.0
Media Player Type	Yes
GPU	Mult-core MaliG51 MP2
СРИ	Hi3751 V811
Memory	4GB DDR4
Storage	32GB (26GB available)
Internal Speakers	5W (x2)
PC Resolution (max)	1920×1080
Mac® Resolution (max)	1920×1080
HDMI 1.4 In	1
HDMI 1.4 (with HDCP 1.4)	1
HDMI 1.4 Out (with HDCP 1.4)	1
3.5mm Audio Out	1
USB 3.0	1
USB 2.0	2
USB 2.0 Type B	1
RS232	1
Ethernet LAN (RJ45)	1
IR in	1
Intel® OPS Slot In (80-pin)	1
Voltage	100-120V+/- 10%, 50/60Hz, 30A
Consumption (max)	1,900W
Consumption (typical)	1,330W
Stand-by	<3W
Temperature	41-104º F (5 - 40º C)
Humidity (non-condensing)	20-80%
Net (lbs)	194.0
Gross (lbs)	397.0
Net (kg)	88.0
Gross (kg)	180.0
Packaging (in.)	57.9 x 26.8 x 33.5
Physical (in.)	95.3 x 57.8 x 1.4

Physical with Wall Mount (in.)	95.3 x 57.8 x 2.2
Packaging (mm)	1470.0 x 680.0 x 850.0
Physical (mm)	2420.0 x 1468.0 x 35.0
Physical with Wall Mount (mm)	2420.0 x 1468.0 x 56.0
Warranty	5-year limited warranty on parts and labor, on-site service
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Package Contents	Power Cord, Remote Control, QSG, Wall-mount x 1, Maintenance Tool (LD-MK-001) x 1, USB Cable (A-to-B) x 1, Spart Modules (LED PCB x 2)
Regulations	cTUVus, FCC, RoHS, Mexico CoC, Mexico Energy
Wifi	802.11ac (2.4GHz/5GHz)
Display Type	Direct View LED
Screen Size	108
Viewable Area (in.)	108
Light Source	Fine Pixel Pitch LED
LED Pitch Size (mm)	1.25
LED Grayscale	14 bits
Display Resolution	1920 x 1080
Refresh Rate	4,440Hz
Aspect Ratio	16:9
Static Contrast Ratio	6,000:1
Backlight Life (Hours)	100,000
Brightness	500 cd/m2
Viewing Angles	160º horizontal, 160º vertical
Operation Rating	24/7









Contact Sales
ViewSonic.com
888.881.8781
email:
salesinfo@viewsonic.com