PX748-4K - 4K UHD PROJECTOR WITH 4000 LUMENS, 240HZ, 4.2MS FOR HOME THEATER AND GAMING

Key **Features**

• High brightness 4000 Lumens 4K UHD projector with high contrast ratio and advanced visual features

• Experience gaming on the big screen with 4.2ms low input lag and a magnificent 240Hz refresh rate

• With a 1.3x optical zoom, anti-warping stabilization and auto H/V keystone, you can project on flat and curved sufaces

• With the ability to decode HDR video signals, this projector delivers incredibly detailed video playback

• Supports media players, gaming consoles, PCs, Macs, and mobile devices with inputs like HDMI, USB C, RJ45, 12V Trigger





30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



3840 x 2160
RESOLUTION



Product **Description**

With incredible Ultra HD resolution, HDR/HLG support, and a high brightness of 4,000 ANSI lumens, the ViewSonic PX748-4K projector delivers stunning home entertainment around the clock: day or night, in bright rooms or dark. With an ultra-low 4.2ms input lag, 240Hz refresh rate, and USB-C connectivity for direct streaming from gaming consoles such as the Nintendo® Switch, this projector provides a whole new level of gaming. Set-up is a breeze too: 1.3x optical zoom, warping capabilities, and H/V keystoning allow for more flexible mounting and easy installation with screen sizes up to 300” on nearly any surface. What’s more, LAN control compatibility and a 12V trigger make this projector a perfect addition to any smart home.

Specifications

More Information

UPC	766907008951
Light Source	DLP Lamp
Display Resolution	4K (3840x2160)
Display Resolution	3840 x 2160
Brightness (Lumens)	4,000 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	0.75m~9.76m (100"@2.50m)
Throw Ratio	1.13-1.47
Keystone	Vertical (+/- 40º) / Horizontal (+/- 40º)
Lens	1.3x optical zoom
Light Source (watt)	240
Light Source Life, Normal (hours)	4000
Light Source Life, Dynamic Eco-Mode (hours)	20000
Color Depth	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio	12,000:1
Aspect Ratio	16:9
Input Lag	37ms
Frequency Horizontal	15K-129KHz
Frequency Vertical	23-240Hz
PC Resolution (max)	3840 x 2160
Mac® Resolution (max)	3840 x 2160
USB 2.0 Type A	1
USB 3.1 Type C	1
Ethernet LAN (RJ45)	1
3.5mm 12V Trigger	1
3.5mm Audio Out	1
Control (RS232)	1
HDMI 2.0 (with HDCP 2.2)	2
Internal Speakers	10W (x1)
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	310W
Stand-by	<0.5W
Physical Controls	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104º F (0 - 40º C)

Humidity (non-condensing)	0-90%
Kensington Lock Slot	1
Net (lbs)	6.2
Gross (lbs)	8.8
Net (kg)	2.8
Gross (kg)	4.0
Packaging (in.)	16.3 x 6.6 x 11.7
Physical (in.)	12.2 x 8.7 x 4.3
Packaging (mm)	415.0 x 168.0 x 297.0
Physical (mm)	312.0 x 222.0 x 108.0
Regulations	FCC, cTUVus, ROHS
Package Contents	Projector, power cable, remote control, USB-C Cable, Quick Start Guide
Warranty	Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907008951







Contact Sales
ViewSonic.com
888.881.8781
email:
salesinfo@viewsonic.com