
CDE7520-W1 - 75" DISPLAY, 3840 X 2160 RESOLUTION, 450 CD/M2 BRIGHTNESS


# Key **Features**

- Ultra HD Resolution
- Powerful Embedded SOC Platform
- All-in-One Solution
- VIEWBOARD ® CAST CONTENT SHARING SOFTWARE
- Remote Content Sharing from Anywhere
- myViewBoard Manager




75"
**DISPLAY**



IPS-Type
**PANEL**



**RESOLUTION**



# Product **Description**

The ViewSonic® CDE7520-W is a 75” premium 4K large format presentation display. With features including a razor-sharp resolution of 3840 x 2160, 450-nit high brightness, 178-degree ultra-wide viewing angles, 2 x 16W speakers, and wireless screen sharing, the CDE7520-W transforms meeting rooms into a dynamic communications hub. The built-in ViewBoard® screen sharing software*, ViewBoard® Cast (along with the optional ViewSonic® vCastSender app) and myViewBoard Display software, enables both on-site and online users to participate in conferences and simultaneously share content. Equipped with twin dual-core processors, 3GB RAM, and 16GB of internal memory, the CDE7520-W can play multimedia from internal storage or a USB flash drive. And with remote configuration and content management system support, the ViewSonic® CDE7520-W is also suitable for a wide array of diverse signage applications. Bundle includes display and USB Wi-Fi adapter. *Chrome, Android, Windows, Mac OS, and iOS compliant

# Specifications

| | More Information |
|---|---|
| **OS** | Android 8.0 |

| | |
|---|---|
| **Media Player Type** | Media Player |
| **GPU** | G51MP2 |
| **CPU** | Dual CPU - Cortex A73 + A5 |
| **CPU Processor Speed** | Quad-core, 1.4GHz |
| **Memory** | 3GB DDR4 |
| **Storage** | 16GB eMMC |
| **Internal Speakers** | 16W (x2) |
| **HDMI 2.0 (with HDCP 2.2)** | 2 |
| **DVI-D** | 1 |
| **VGA** | 1 |
| **DisplayPort** | 1 |
| **RCA Audio Out** | 1 |
| **3.5mm Audio In** | 1 |
| **SPDIF Audio Out** | 1 |
| **SPDIF** | 1 |
| **USB 3.0** | 1 |
| **USB 2.0** | 2 |
| **OPS PC Slot** | 1 |
| **RS232** | 1 |
| **Ethernet LAN (RJ45)** | 1 |
| **IR in** | 1 |
| **IR out** | 1 |
| **WIFI Module Slot** | 1 |
| **Voltage** | 100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz |
| **Consumption (max)** | 300W |
| **Consumption (typical)** | 240W |
| **Stand-by** | <0.5W |
| **Temperature** | 32-104º F (0 - 40º C) |
| **Humidity (non-condensing)** | 20-80% |
| **Net (lbs)** | 64.6 |
| **Gross (lbs)** | 91.9 |
| **Net (kg)** | 29.3 |
| **Gross (kg)** | 41.7 |
| **Packaging (in.)** | 72.0 x 43.2 x 8.7 |
| **Physical (in.)** | 65.8 x 37.6 x 2.8 |
| **Packaging (mm)** | 1828.0 x 1098.0 x 220.0 |

| | |
|---|---|
| **Physical (mm)** | 1672.0 x 955.0 x 70.0 |
| **VESA Compatible** | 400 x 200 mm |
| **Screw Size** | M8 |
| **AV Control** | AMX Certified, Crestron Certified (Version 1.0), Extron Certified |
| **Warranty** | Three (3) years from the date of first consumer purchase for parts and labor. |
| **Recycle/Disposal** | Please dispose of in accordance with local, state or federal laws. |
| **Package Contents** | CDE7520-W, Remote control with batteries, Quick Start Guide, Power cable, HDMI Cable, Wall Mount Screws and RS232 cable |
| **Regulations** | cULus, FCC, Energy Star, RoHS |
| **Display Type** | LCD |
| **Screen Size** | 75" |
| **Viewable Area (in.)** | 75 |
| **Orientation** | Landscape |
| **Colors** | 1.07B |
| **Color Space Support** | 8 bit+FRC |
| **Light Source** | DLED |
| **Display Resolution** | 3840 x 2160 |
| **Panel Type** | IPS-Type |
| **Aspect Ratio** | 16:9 |
| **Static Contrast Ratio** | 1,200:1 |
| **Backlight Life (Hours)** | 50,000 |
| **Brightness** | 450 cd/m2 |
| **Response Time (Typical GTG)** | 8ms |
| **Viewing Angles** | 178º horizontal, 178º vertical |
| **Panel Surface** | Hard Coat - Anti-Glare, 3% Haze, 2H with anti-glare treatment |








**Contact Sales**
ViewSonic.com
888.881.8781
email:
salesinfo@viewsonic.com