



LS625X-S


Key Features



60 - 300 in. / 1.5 - 7.6 m
DISPLAY



PANEL



1920 x 1080
RESOLUTION



Product Description

Featuring 1024x768 XGA resolution and 3,200 lumens of brightness, the ViewSonic® LS625X short throw laser projector is an ideal projection solution for education environments. Designed with a laser phosphor light source lasting up to 20,000 hours, and a sealed optical engine with a waveform air filter that protects against dust and moisture, this projector delivers long-term, virtually maintenance-free usage for any classroom. With its 0.49 short throw ratio and horizontal/vertical keystoneing, the LS625X makes installation a hassle-free experience. What's more, the short throw ratio allows you to place the projector just a few feet from a wall or screen to give you a huge image for less cost than a comparably sized display. Crestron and AMX certification delivers network management capabilities, while exclusive SuperColor™ technology offers a wide color range for true-to-life images in any classroom.

Specifications

More Information

UPC
Light Source

766907003703

DLP Laser

Display Resolution	XGA (1024x768)
Display Resolution	1024 x 768
Brightness (Lumens)	3,200 ANSI
Screen Size	60 - 300 in. / 1.5 - 7.6 m
Throw Distance	2.1 - 10.4 ft / 0.6 - 3.2 m
Throw Ratio	0.49
Keystone	Vertical (+/- 40°)
Lens	Fixed Zoom
Light Source Life, Normal (hours)	20000
Light Source Life, Dynamic Eco-Mode (hours)	20000
Color Depth	1.07B Color (R/G/B 10bit)
Aspect Ratio	4:3
Input Lag	37ms
Frequency Horizontal	15K~102KHz
Frequency Vertical	23~120Hz
PC Resolution (max)	1920 x 1080
Mac® Resolution (max)	1920 x 1080
Ethernet LAN (RJ45)	1
3.5mm 12V Trigger	1
3.5mm Audio Out	1
3.5mm Audio In	1
Control (RS232)	1
HDMI 1.4 In	1
HDMI 1.4 (with HDCP 1.4)	1
VGA In	2
VGA Out	1
Composite RCA Video In	1
S-Video In	1
Mini USB	1
Internal Speakers	10W (x1)
Consumption (typical)	305W
Stand-by	<0.5W
Physical Controls	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104° F (0 - 40° C)

Humidity (non-condensing)	0-90%
Kensington Lock Slot	1
Net (lbs)	13.6
Gross (lbs)	15.4
Net (kg)	6.2
Gross (kg)	7.0
Packaging (in.)	19.1 x 9.4 x 15.4
Physical (in.)	15.1 x 5.8 x 11.5
Packaging (mm)	485.0 x 238.0 x 390.0
Physical (mm)	383.0 x 147.0 x 291.0
AV Control	AMX Certified, Crestron Certified, PJ Link Certified
Regulations	FCC, cTUVus, ROHS
Package Contents	LS625X projector, power cable, VGA cable, remote control, Quick Start Guide
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Classification	Refurbished

UPC: 766907003703



Contact Sales

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com