

LS610WH - 4000 ANSI LUMENS WXGA LED PROJECTOR WITH H/V KEYSTONE, 4 CORNER ADJUSTMENT

Key Features


- High brightness 4000 Lumens WXGA LED projector with advanced visual features
- Latest LED technology provides an extended lifespan of up to 60,000 hours
- 1.2x optical zoom, 4 corner adjustment, and a 40-degree H/V keystone and 360 degree projection
- This projector can be configured to automatically turn on and off
- Schedule, and manage the projector remotely with Crestron, AMX, Extron, PJ Link, ATEN, and ViewSonic's vController
- Supports most media players, PCs, Macs, and mobile devices with inputs such as HDMI, USB, Ethernet LAN



30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



1920 x 1080
RESOLUTION



Product Description

Featuring 1280x800 WXGA resolution and 4,000 ANSI lumens of brightness, the ViewSonic® LS610WH is a lamp-free LED projector ideal for business and education. With 3rd generation LED technology, the LS610WH eliminates the need to continuously swap out bulbs and dispose of toxic chemicals. In addition, an IP5X sealed optical engine prevents dust and moisture from entering the projector, ensuring impeccable image quality and a long maintenance-free lifespan of up to 60,000 hours.* An automatic on/off feature delivers efficiency and power savings, while 360° tilt angle projection delivers flexible setup in small- to medium-sized meeting rooms and classrooms. Whether for business or education, the ViewSonic LS610WH LED projector provides a picture-perfect presentation every time.

*Lightsource lifespan may vary based on actual usage and other factors.

Specifications

| | More Information |
|----------------------------|------------------------------|
| UPC | 766907018141 |
| Light Source | LED |
| Display Resolution | WXGA (1280x800) |
| Display Resolution | 1280 x 800 |
| Brightness (Lumens) | 4,000 ANSI |
| Screen Size | 30 - 300 in. / 0.76 - 7.62 m |
| Throw Distance | 0.88m-10.59m (100"@2.95m) |

| | |
|--|--|
| Throw Ratio | 1.37-1.64 |
| Keystone | Vertical (+/- 40°) / Horizontal (+/- 40°) |
| Lens | 1.2x optical zoom |
| Light Source (watt) | RGBB LED |
| Light Source Life, Normal (hours) | 60,000 |
| Color Depth | 1.07 Billion Colors |
| Dynamic Contrast Ratio | 3,000,000:1 |
| Aspect Ratio | 16:10 |
| Input Lag | 37ms |
| Frequency Horizontal | 15K~102KHz |
| Frequency Vertical | 23-120Hz |
| PC Resolution (max) | 1920 x 1080 |
| Mac® Resolution (max) | 1920 x 1080 |
| USB 2.0 Type A | 1 |
| Ethernet LAN (RJ45) | 1 |
| 3.5mm Audio Out | 1 |
| 3.5mm Audio In | 1 |
| Control (RS232) | 1 |
| HDMI 1.4 (with HDCP 1.4) | 2 |
| Internal Speakers | 10W (x1) |
| Voltage | 100-240V+/- 10%, 50/60Hz AC |
| Consumption (typical) | 310W |
| Stand-by | <0.5W |
| Physical Controls | Keypad, Power key |
| On Screen Display | Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality) |
| Temperature | 32-104° F (0 - 40° C) |
| Kensington Lock Slot | 1 |
| Net (lbs) | 11.0 |
| Gross (lbs) | 15.4 |
| Net (kg) | 5.0 |
| Gross (kg) | 7.0 |
| Packaging (in.) | 19.3 x 14.8 x 10.6 |
| Physical (in.) | 15.2 x 10.9 x 4.6 |
| Packaging (mm) | 490 x 376 x 268.0 |
| Physical (mm) | 386.0 x 276.0 x 116.0 |

Regulations

cTUVus

Package Contents

LS610WH projector, power cable, remote control, Quick Start Guide

Warranty

Three-year limited warranty on parts and labor, 1-year limited warranty on the light source, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

Recycle/Disposal

Please dispose of in accordance with local, state or federal laws.

UPC: 766907018141



Contact Sales

ViewSonic.com

888.881.8781 

email: salesinfo@viewsonic.com 