LS751HD - 5,000 ANSI LUMENS 1080P LASER BUSINESS/EDUCATION PROJECTOR

Key **Features**

• High brightness 5000 Lumens 1080p laser projector with advanced visual features

• Long-lasting laser phosphor light source allows the lamp to shine bright for up to 30,000 hours

• 1.6x optical zoom, 4 corner adjustment, 40-degree H/V keystone, V lens shift and 360 degree projection

• This projector can be configured to automatically turn on and off

• Schedule, and manage the projector remotely with Crestron, AMX, Extron, PJ Link, ATEN, and ViewSonic's vControlller

• Supports most media players, PCs, Macs, and mobile devices with inputs such as HDMI, USB, Ethernet LAN



30 - 300 in. / 0.76 - 7.62 m
DISPLAY

PANEL

VGA(640 x 480) to 4K UHD (3840 x 2160)
RESOLUTION

FLEXIBLE CONNECTIVITY
for your favorite devices

Product **Description**

Experience better brightness on a smaller budget with the ViewSonic® LS751HD laser projector. This state-of-the-art projector delivers a stunning 5,000 ANSI lumens for crystal clear images even in bright rooms. Experience stunning 300" images with breathtaking colors for boardrooms, lecture halls and other public spaces on a long-lasting, eco-friendly projection solution that's designed for 24/7 usage. Enjoy versatile installation options with vertical lens shift, 1.6x optical zoom, easy image adjustment and 360° projection. HDMI 2.0b connectivity ensures access to 4K content with HDR/HLG support.

Specifications

More Information

UPC	766907019940

Light Source	Laser
Display Resolution	Full HD (1920x1080)
Display Resolution	1920 x 1080
Brightness (Lumens)	5,000 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	0.93-14.88m (100"@3.10m)
Throw Ratio	1.3-1.56
Keystone	Vertical (± 30º) / Horizontal (± 30º)
Lens	1.6x optical zoom
Light Source Life, Normal (hours)	20000
Light Source Life, Dynamic Eco-Mode (hours)	30000
Color Depth	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio	3,000,000:1
Aspect Ratio	16:9
Input Lag	37ms
Frequency Horizontal	15K~102KHz
Frequency Vertical	23-120Hz
PC Resolution (max)	VGA(640 x 480) to 4K UHD (3840 x 2160)
Mac® Resolution (max)	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4K UHD
USB 2.0 Type A	1
Ethernet LAN (RJ45)	1
3.5mm Audio Out	1
Control (RS232)	1
HDMI 1.4 (with HDCP 1.4)	2
Internal Speakers	15W (x1)
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	245W
Stand-by	<0.5W
Physical Controls	Keypad, Power key
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104º F (0 - 40º C)
Kensington Lock Slot	1
Net (lbs)	9.9
Gross (lbs)	14.6
Net (kg)	4.5

Gross (kg)	6.6
Packaging (in.)	19.5 x 7.7 x 15.2
Physical (in.)	13.3 x 10.4 x 5.2
Packaging (mm)	496 x 195 x 387
Physical (mm)	337 x 265 x 131.5
Regulations	cTUVus
Package Contents	Projector, power cable, remote control, Quick Start Guide
Warranty	Three-year limited warranty on parts and labor, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907019940



IMAGE SIZE AND PROJECTOR DISTANCE

5000 LUMENS
and Full HD (1920x1080) Resolution

Contact Sales

ViewSonic.com
888.881.8781
email:
salesinfo@viewsonic.com