



VX2767U-2K - 27" 2K QHD THIN-BEZEL IPS MONITOR WITH USB-C, HDMI, AND DISPLAYPORT

Key Features


- 27-inch QHD (2560x1440p) IPS monitor with thin bezels and 75Hz refresh rate
- USB-C connectivity for fast data, audio and video transfer, and 65W charging over one cable
- HDR10 content support for deep contrast, rich color, and vibrant details
- Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- The VX2767u-2k supports laptops, PCs, and Macs with USB-C, HDMI, and DisplayPort inputs



27
DISPLAY



IPS
PANEL



2560 X 1440
RESOLUTION



Product Description

Designed for the modern-day home office, the ViewSonic® VX2767u-2k is a 27" Quad HD IPS monitor that combines style with optimal versatility and functionality. With a 3-sided frameless design, this monitor provides a near-seamless viewing experience ideal for multi-monitor setups. The latest USB 3.2 Type-C connectivity delivers 65W charging power, video, and audio over a single cable, while HDMI and DisplayPort inputs keep you connected to your favorite devices. Moreover, HDR10 content support delivers vivid colors and brightness that exceed standard monitors.

Specifications

More Information

UPC

766907021028

| | |
|------------------------------------|---|
| Screen Size | 27 |
| Viewable Area (in.) | 27 |
| Panel Type | IPS |
| Display Resolution | 2560 x 1440 |
| Display Resolution | QHD (2560x1440) |
| Static Contrast Ratio | 1,000:1 |
| Dynamic Contrast Ratio | 50,000,000:1 |
| Light Source | LED |
| Brightness | 250 cd/m2 |
| Colors | 16.7M |
| Color Space Support | 8 bit |
| Aspect Ratio | 16:9 |
| Response Time (Typical GTG) | 4ms |
| Response Time (MPRT) | 1ms |
| Viewing Angles | 178º horizontal, 178º vertical |
| Backlight Life (Hours) | 30,000 |
| Panel Surface | Anti-Glare type, Hard-coating (3H), Haze 25% |
| PC Resolution (max) | 2560 X 1440 |
| Mac® Resolution (max) | 2560 X 1440 |
| USB Type C | 65W x 1 |
| 3.5mm Audio Out | 1 |
| HDMI 1.4 In | 1 |
| DisplayPort | 1 |
| Internal Speakers | 2.5W (x2) |
| Eco Mode (Conserve) | 16W |
| Eco Mode (optimized) | 18W |
| Consumption (typical) | 21W |
| Consumption (max) | 26W |
| Voltage | AC 100-240V (universal), 50-60Hz |
| Stand-by | 0.5W |
| Power Supply | Internal |
| Cable Organization | No |
| Kensington Lock Slot | 1 |
| Physical Controls | Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) |
| On Screen Display | Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu |
| Temperature | 32-104º F (0 - 40º C) |

| | |
|-------------------------------------|---|
| Humidity (non-condensing) | 20-90% |
| VESA Compatible | 100 x 100 mm |
| Frequency Horizontal | HDMI (v1.4): 24 ~ 113 KHz, DisplayPort: 24 ~ 113 KHz, USB-C: 24 ~ 113 KHz |
| Frequency Vertical | HDMI (v1.4): 48 ~ 75 Hz, DisplayPort: 48 ~ 75 Hz, USB-C: 48 ~ 75 Hz |
| Tilt (Forward/Back) | 5° / 20° |
| Net (lbs) | 11.7 |
| Net Without Stand (lbs) | 10.4 |
| Gross (lbs) | 13.9 |
| Net (kg) | 5.3 |
| Net Without Stand (kg) | 4.7 |
| Gross (kg) | 6.3 |
| Packaging (in.) | 27.6 x 18.1 x 4.6 |
| Physical (in.) | 24.2 x 17.2 x 8.7 |
| Physical Without Stand (in.) | 24.2 x 14.4 x 2.1 |
| Packaging (mm) | 701.0 x 461.0 x 118.0 |
| Physical (mm) | 614.0 x 436.0 x 222.0 |
| Physical Without Stand (mm) | 614.0 x 366.0 x 53.0 |
| Regulations | cTUVus, FCC-B, ICES003, Energy Star 8.0, CEC, NOM, Mexico Energy |
| Package Contents | VX2767U-2K Display, Power Cable, USB-C Cable, HDMI Cable, Quick Start Guide |
| Recycle/Disposal | Please dispose of in accordance with local, state or federal laws. |
| UPC: 766907021028 | |



Contact Sales
[ViewSonic.com](https://www.viewsonic.com)
 888.881.8781
 email:
salesinfo@viewsonic.com