

## VP2468A\_H2 - 24" COLORPRO™ 1080P DUAL PACK HEAD-ONLY IPS DOCKING MONITORS WITH 65W USB-C AND DAISY CHAIN

### Key Features

---


- Sold as a dual pack without monitor stands for easy dual-screen installation
- Single-cable USB-C connectivity for video, audio, data and up to 65W power delivery
- Pantone Validated display with Delta E<2 color accuracy
- Convenient VESA compatibility for easy mounting and installation



24  
DISPLAY



IPS  
PANEL



1920 x 1080  
RESOLUTION



### Product Description

---

If you're looking for professional dual monitors that deliver unmatched color accuracy, as well as easy deployment and mounting capabilities, look no further than the ViewSonic® VP2468a\_H2. Sold as a dual pack of monitors without monitor stands, VP2468a\_H2 requires less packaging for a reduced environmental footprint, while still providing VESA-compatible mounting for easy installation. USB-C connectivity helps to simplify your workspace by delivering audio, video, data and up to 65W of power delivery over a single universal cable. In addition, DisplayPort out enables seamless daisy chaining dual-monitor setup, while edge-to-edge SuperClear® IPS panels and ultra-thin bezels provide a sleek and frameless viewing experience. To ensure precise, uniform color, these monitors are factory calibrated to deliver an amazing Delta E<2 value. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors.

# Specifications

	More Information
<b>UPC</b>	766907019636
<b>Screen Size</b>	24
<b>Viewable Area (in.)</b>	23.8
<b>Panel Type</b>	IPS
<b>Display Resolution</b>	1920 x 1080
<b>Display Resolution</b>	Full HD (1920x1080)
<b>Static Contrast Ratio</b>	1,000:1
<b>Dynamic Contrast Ratio</b>	20M:1
<b>Light Source</b>	LED
<b>Brightness</b>	250 cd/m2
<b>Colors</b>	16.7M
<b>Color Space Support</b>	8 bit (6 bit + A-FRC)
<b>Aspect Ratio</b>	16:9
<b>Response Time (Typical GTG)</b>	5ms
<b>Viewing Angles</b>	178° horizontal, 178° vertical
<b>Backlight Life (Hours)</b>	30,000
<b>Panel Surface</b>	Anti-Glare type, Hard-coating (3H), Haze 25%
<b>Refresh Rate</b>	60Hz
<b>PC Resolution (max)</b>	1920 x 1080
<b>Mac® Resolution (max)</b>	1920 x 1080
<b>USB Type A</b>	2
<b>USB Type C</b>	1
<b>3.5mm Audio Out</b>	1
<b>Ethernet LAN (RJ45)</b>	1
<b>HDMI 1.4 In</b>	1
<b>DisplayPort</b>	1
<b>DisplayPort Out</b>	1
<b>Eco Mode (Conserve)</b>	8.9w
<b>Eco Mode (optimized)</b>	10.8w
<b>Consumption (typical)</b>	13.9w
<b>Consumption (max)</b>	15.4w
<b>Voltage</b>	AC 100-240V (universal), 50-60Hz
<b>Stand-by</b>	0.5w

<b>Power Supply</b>	Internal
<b>Cable Organization</b>	No
<b>Kensington Lock Slot</b>	1
<b>Physical Controls</b>	Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)
<b>On Screen Display</b>	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Humidity (non-condensing)</b>	20-90%
<b>VESA Compatible</b>	100 x 100 mm
<b>Frequency Horizontal</b>	15 ~ 90 KHz
<b>Frequency Vertical</b>	24 ~ 75 Hz
<b>Net Without Stand (lbs)</b>	15.3
<b>Gross (lbs)</b>	24.2
<b>Net Without Stand (kg)</b>	7
<b>Gross (kg)</b>	11
<b>Packaging (in.)</b>	25 " (W) x 16.5 " (H) x 9.9 " (D)
<b>Physical Without Stand (in.)</b>	21.2 " (W) x 12.2 " (H) x 1.9 " (D)
<b>Packaging (mm)</b>	635 mm (W) x 420 mm (H) x 252 mm (D)
<b>Physical Without Stand (mm)</b>	539 mm (W) x 311 mm (H) x 48 mm (D)
<b>Regulations</b>	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, MX-CoC, Mexico Energy
<b>Package Contents</b>	LCD Display x2, Power Cable x2, DP to DP Cable x2, USB Type C Cable x2, Quick Start Guide
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.
<b>Warranty</b>	Three-year limited warranty on parts, labor and backlight

UPC: 766907019636



**Contact Sales**  
[ViewSonic.com](http://ViewSonic.com)

888.881.8781  
 email:  
[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)