


VP3256-4K - 32" COLORPRO™ 4K UHD IPS MONITOR WITH 60W USB-C, sRGB, HDR10 AND PANTONE VALIDATED

Key Features



32"
DISPLAY



IPS
PANEL



3840 x 2160
RESOLUTION



Product Description


Engineered to deliver unmatched color accuracy crucial for professional applications, the ViewSonic® VP3256-4K UHD monitor displays your work with the vivid and lifelike color it deserves. With a SuperClear® IPS panel for 100% sRGB and a sleek 3-sided frameless design, the VP3256-4K provides a near-seamless viewing experience. The VP3256-4K is equipped with USB-C for single cable connectivity to deliver video, audio, and 65W of power delivery. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E <2, so you can be confident what you see on screen is what your customers will see, as well.

Specifications

UPC	766907017991
Screen Size	32"
Viewable Area (in.)	31.5
Panel Type	IPS
Display Resolution	3840 x 2160
Display Resolution	4K (3840x2160)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	20,000,000:1
Light Source	LED
Brightness	350 cd/m2
Colors	1.07B
Color Space Support	10 bit (8 bit + A-FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
PC Resolution (max)	3840 x 2160
Mac® Resolution (max)	3840 x 2160
USB Type A	2
USB Type B	1
USB Type C	65W x 1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	3W (x2)
Eco Mode (Conserve)	32W
Eco Mode (optimized)	39W
Consumption (typical)	46W
Consumption (max)	125W
Voltage	100-240 VAC
Stand-by	0.5W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (power), Key 2, Key 3, Key 4, Key 5 (favorite)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	TMDS, PCI-E, Micro-Packet: 15 ~ 136 KHz
Frequency Vertical	TMDS, PCI-E, Micro-Packet: 24 ~ 75 Hz
Height Adjust	130 mm / 5.1 in
Swivel	120°
Pivot (Right/Left)	90° / 90°
Regulations	cTUVus, FCC-B, ICES003, CEC, MX-CoC, Mexico Energy
Net (lbs)	24.0
Net Without Stand (lbs)	15.8
Gross (lbs)	33.7
Net (kg)	10.9
Net Without Stand (kg)	7.2
Gross (kg)	15.3
Packaging (in.)	33.1 x 20.5 x 12.8
Physical (in.)	28.2 x 20.2~25.4 x 10.4
Physical Without Stand (in.)	28.2 x 16.7 x 2.6
Packaging (mm)	840.0 x 520.0 x 326.0
Physical (mm)	715.0 x 514.0~644.0 x 265.0
Physical Without Stand (mm)	715.0 x 423.0 x 66.0
Package Contents	VP3256-4K, Power Cable, USB-C Cable, HDMI cable
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907017991



Contact Sales
ViewSonic.com
 888.881.8781
 email:
salesinfo@viewsonic.com