

VG2756-2K-S

Key Features

- Streamlined Desktop Display Solution
- Enhanced Productivity with Dual Monitor Setup
- Reduce Clutter with Single-Cable Solution
- A More Comfortable Workspace
- Command and Control Made Easy
- Minimized Total Cost of Ownership



27
DISPLAY



IPS
PANEL



2560 x 1440
RESOLUTION



Product Description

Designed to boost productivity and maximize output, the ViewSonic® VG2756-2K is a 27" QHD docking monitor that transforms your desktop into a streamlined and efficient workspace. Enjoy reliable and flexible network connectivity with the integrated gigabit Ethernet port, while the latest USB Type-C connectivity and Daisy Chain capability makes dual-monitor setup a breeze. That's not all, the integrated USB hub also provides single-cable simplicity for connecting and charging your peripherals and accessories. A best-in-class ergonomic design features 40-degree tilt and bi-directional pivot so your screen and workspace are as comfortable as you need. In addition, the included vDisplay software gives you quick and easy OSD control, as well as customized screen templates for easy multi-tasking. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for quick deployment and a lower total cost of ownership.

Specifications

UPC	766907011135
Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	QHD (2560x1440)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	LED
Brightness	350 cd/m2
Colors	16.7M
Color Space Support	8 Bit
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	2560 x 1440
Mac® Resolution (max)	2560 x 1440
USB Type A	2
USB Type B	1
USB Type C	1
Ethernet LAN (RJ45)	1
HDMI 1.4 In	1
DisplayPort	1
DisplayPort Out	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	16.8
Eco Mode (optimized)	21.2
Consumption (typical)	30.7
Consumption (max)	67.0
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	Internal
Cable Organization	No

Kensington Lock Slot	1
Physical Controls	1,2,3,4,5,6 (Power)
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 90 KHz
Frequency Vertical	49 ~ 75 Hz
Digital Sync	TMDS for HDMI (v1.4), PCI-E for DisplayPort (v1.2), Micro-Packet for USB Type C
Height Adjust	130 mm / 5.1 in
Swivel	120º
Pivot (Right/Left)	90º / 90º
Tilt (Forward/Back)	40º / 5º
Net (lbs)	15.2
Net Without Stand (lbs)	9.9
Gross (lbs)	22.5
Net (kg)	6.9
Net Without Stand (kg)	4.5
Gross (kg)	10.2
Packaging (in.)	27.2 x 8.6 x 16.9
Physical (in.)	24.1 x 16.0 x 8.0
Physical Without Stand (in.)	24.1 x 14.3 x 2.0
Packaging (mm)	692.0 x 218.0 x 430.0
Physical (mm)	613.0 x 406.0 x 202.0
Physical Without Stand (mm)	613.0 x 363.0 x 52.0
Regulations	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, MX-CoC, Mexico Energy
Package Contents	VG2756-2K, Power Cable, DP to DP Cable, USB Type C cable, USB Type B Uplink Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
Classification	Refurbished

UPC: 766907011135



Contact Sales

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com