


VX2718-P-MHD - 27" 1080P 1MS 165HZ GAMING MONITOR WITH FREESYNC


Key Features



27"
DISPLAY



MVA
PANEL



1920x1080
RESOLUTION



Product Description

The ViewSonic® VX2718-P-MHD is a 27" 1080p gaming monitor built for gaming and entertainment. With a sleek frameless design, the VX2718-P-MHD provides a seamless viewing experience for multi-monitor gaming setups. Featuring a 165Hz* refresh rate, 1ms (MPRT) response time and FreeSync Premium technology, this monitor virtually eliminates screen tearing and stuttering for a fluid gaming experience. The VX2718-P-MHD also comes equipped with ViewSonic exclusive ViewMode™ presets, which offer optimized screen performance for different home entertainment applications such as watching movies, editing files, or playing video games. Two HDMI (v1.4) inputs, and one DisplayPort (v1.2) input offers flexible connectivity for both general use and entertainment. *165Hz refresh rate with DisplayPort

Specifications

UPC	766907013597
Monitor Series	OMNI Gaming
Screen Size	27"
Viewable Area (in.)	27
Panel Type	MVA
Display Resolution	1920 x 1080
Display Resolution	Full HD (1920x1080)
Static Contrast Ratio	4,000:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Color Space Support	8 bit (6 bit + FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Response Time (MPRT)	1ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate	165Hz
PC Resolution (max)	1920x1080
Mac® Resolution (max)	1920x1080
3.5mm Audio Out	1
HDMI 1.4 In	2
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	26W
Eco Mode (optimized)	28W
Consumption (typical)	32W
Consumption (max)	37W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)

On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI (v1.4): 24 ~ 166.4 KHz, DisplayPort (v1.2): 24 ~ 183 KHz
Frequency Vertical	HDMI (v1.4): 50 ~ 144 Hz, DisplayPort (v1.2): 50 ~ 165 Hz
Tilt (Forward/Back)	5º / 25º
Regulations	cTUVus, FCC-B, ICES003, CEC, NOM, Mexico Energy
Net (lbs)	4.4
Net Without Stand (lbs)	4.0
Gross (lbs)	6.0
Net (kg)	9.7
Net Without Stand (kg)	8.8
Gross (kg)	13.2
Packaging (in.)	27.4 x 18.1 x 5.7
Physical (in.)	24.2 x 18.0 x 8.9
Physical Without Stand (in.)	24.2 x 14.3 x 1.8
Packaging (mm)	695.0 x 460.0 x 145.0
Physical (mm)	615.0 x 458.0 x 226.0
Physical Without Stand (mm)	615.0 x 364.0 x 46.0
Package Contents	VX2718-P-MHD, Power Cable, DisplayPort Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907013597



GREAT VISUALS
For home entertainment and gaming



Contact Sales
[ViewSonic.com](https://www.viewsonic.com)
888.881.8781
email: salesinfo@viewsonic.com