





## VG2455-2K - 24" 1440P ERGONOMIC 40-DEGREE TILT IPS MONITOR WITH USB C

### Key Features


---



24"  
**DISPLAY**



IPS  
**PANEL**



2560x1440  
**RESOLUTION**

WQHD (2560x1440p) Resolution



### Product Description

---

Designed for the modern day office, the ViewSonic® VG2455-2K monitor delivers an efficient end-to-end enterprise experience. USB Type-C connectivity provides charging power, video, and audio over a single connector for convenience and reduced cable clutter. SuperClear® IPS panel technology delivers wide-angle viewing and incredibly vivid colors, while 3-sided thin bezel design provides a seamless viewing experience for multi-monitor setups. For enhanced productivity, an advanced ergonomic design offers a wide range of customizable adjustments for maximum comfort including pivot, swivel, height adjustment, and tilt. With the ability to tilt an impressive 40-degrees, this 24" monitor is ideal for users who prefer to work while standing up, as well as for those who like to use their screen for group discussions. Along with USB Type-C, additional connectivity options include HDMI, DisplayPort, and USB. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for simple out-of-the box setup. The quick release stand also includes an integrated client mount and cable management features.

# Specifications

|                             | More Information                 |
|-----------------------------|----------------------------------|
| UPC                         | 766907002652                     |
| Screen Size                 | 24"                              |
| Viewable Area (in.)         | 23.8                             |
| Panel Type                  | IPS                              |
| Display Resolution          | 2560 x 1440                      |
| Display Resolution          | QHD (2560x1440)                  |
| Static Contrast Ratio       | 1,000:1                          |
| Dynamic Contrast Ratio      | 80,000,000:1                     |
| Light Source                | WLED                             |
| Brightness                  | 300 cd/m2                        |
| Colors                      | 16.7M                            |
| Color Space Support         | True 8 bit                       |
| Aspect Ratio                | 16:9                             |
| Response Time (Typical GTG) | 15ms                             |
| Response Time (GTG w/OD)    | 5ms                              |
| Viewing Angles              | 178º horizontal, 178º vertical   |
| Backlight Life (Hours)      | 30,000                           |
| Panel Surface               | Anti-glare, Hard coating (3H)    |
| PC Resolution (max)         | 2560x1440                        |
| Mac® Resolution (max)       | 2560x1440                        |
| USB Type A                  | 3                                |
| USB Type B                  | 1                                |
| USB Type C                  | 60W x 1                          |
| HDMI 1.4 In                 | 1                                |
| DisplayPort                 | 1                                |
| Internal Speakers           | 2W (x2)                          |
| Eco Mode (Conserve)         | 17.7 W                           |
| Eco Mode (optimized)        | 21.8 W                           |
| Consumption (typical)       | 27.4 W                           |
| Consumption (max)           | 58.5 W                           |
| Voltage                     | AC 100-240V (universal), 50-60Hz |
| Stand-by                    | 0.3 W                            |
| Power Supply                | Internal                         |

|                                     |                                                                                                                                                                                                                      |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Cable Organization</b>           | No                                                                                                                                                                                                                   |
| <b>Kensington Lock Slot</b>         | 1                                                                                                                                                                                                                    |
| <b>Physical Controls</b>            | 1,2,3,4,5,6 (Power)                                                                                                                                                                                                  |
| <b>On Screen Display</b>            | Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) |
| <b>Temperature</b>                  | 32-104º F (0 - 40º C)                                                                                                                                                                                                |
| <b>Humidity (non-condensing)</b>    | 20-90%                                                                                                                                                                                                               |
| <b>VESA Compatible</b>              | 100 x 100 mm                                                                                                                                                                                                         |
| <b>Frequency Horizontal</b>         | 15 ~ 90 KHz                                                                                                                                                                                                          |
| <b>Frequency Vertical</b>           | 49 ~ 75 Hz                                                                                                                                                                                                           |
| <b>Digital Sync</b>                 | TMDS for HDMI (v1.4), PCI-E for DisplayPort (v1.2), Micro-Packet for USB Type C                                                                                                                                      |
| <b>Height Adjust</b>                | 130 mm / 5.1 in                                                                                                                                                                                                      |
| <b>Swivel</b>                       | 120º                                                                                                                                                                                                                 |
| <b>Pivot (Right/Left)</b>           | 90º / 90º                                                                                                                                                                                                            |
| <b>Tilt (Forward/Back)</b>          | 40º / 5º                                                                                                                                                                                                             |
| <b>Regulations</b>                  | cTUVus, FCC-B, ICES003, Energy Star Certified, EPEAT Certified, MX-CoC, Mexico Energy                                                                                                                                |
| <b>Net (lbs)</b>                    | 14.1                                                                                                                                                                                                                 |
| <b>Net Without Stand (lbs)</b>      | 8.8                                                                                                                                                                                                                  |
| <b>Gross (lbs)</b>                  | 20.7                                                                                                                                                                                                                 |
| <b>Net (kg)</b>                     | 6.4                                                                                                                                                                                                                  |
| <b>Net Without Stand (kg)</b>       | 4.0                                                                                                                                                                                                                  |
| <b>Gross (kg)</b>                   | 9.4                                                                                                                                                                                                                  |
| <b>Packaging (in.)</b>              | 23.4 x 8.3 x 15.6                                                                                                                                                                                                    |
| <b>Physical (in.)</b>               | 21.2 x 16.0 x 8.0                                                                                                                                                                                                    |
| <b>Physical Without Stand (in.)</b> | 21.2 x 12.6 x 2.0                                                                                                                                                                                                    |
| <b>Packaging (mm)</b>               | 595.0 x 210.0 x 396.0                                                                                                                                                                                                |
| <b>Physical (mm)</b>                | 539.0 x 406.2 x 202.0                                                                                                                                                                                                |
| <b>Physical Without Stand (mm)</b>  | 539.0 x 320.0 x 52.0                                                                                                                                                                                                 |
| <b>Package Contents</b>             | VG2455-2K, Power Cable, USB Type-C Cable, HDMI Cable, USB Upstream Cable, Quick Start Guide                                                                                                                          |
| <b>Recycle/Disposal</b>             | Please dispose of in accordance with local, state or federal laws.                                                                                                                                                   |
| <b>Warranty</b>                     | *Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.                                                                                                                   |

UPC: 766907002652



**Contact Sales**  
[ViewSonic.com](https://www.viewsonic.com)  
888.881.8781 📞  
email:  
[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)