





PG707W - 4000 LUMENS WXGA NETWORKABLE PROJECTOR WITH 1.3X OPTICAL ZOOM AND LOW INPUT LAG


Key Features



30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



1920 x 1080
RESOLUTION

Flexible connectivity for your favorite devices.



Product Description

The ViewSonic® PG707W projector features 4,000 lumens, WXGA 1280 x 800 native resolution, an intuitive, user-friendly design, and a sleek white chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. An energy-saving SuperEco™ feature reduces power consumption and extends the lamp life by up to 20,000 hours. A 10W speaker delivers incredibly clear and audible sound, while a top lamp door enables easy access for lamp maintenance. The PG707W is the ideal high brightness projector for use in both classroom and corporate settings.

Specifications

[More Information](#)

UPC	766907007664
Light Source	DLP Lamp
Display Resolution	WXGA (1280x800)
Display Resolution	1280 x 800
Brightness (Lumens)	4,000 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	2.6 - 33.1 ft / .8 - 10.1 m
Throw Ratio	1.21-1.57
Keystone	Vertical (+/- 40º) / Horizontal (+/- 40º)
Lens	1.3x optical zoom
Light Source (watt)	203
Light Source Life, Normal (hours)	6000
Light Source Life, Dynamic Eco-Mode (hours)	20000
Color Depth	1.07 Billion Colors
Dynamic Contrast Ratio	22,000:1
Aspect Ratio	16:10
Input Lag	37ms
Frequency Horizontal	15K~105KHz
PC Resolution (max)	1920 x 1080
PC Resolution (min)	640 x 480
Mac® Resolution (max)	1920 x 1080
Mac® Resolution (min)	640 x 480
USB 2.0 Type A	1
Ethernet LAN (RJ45)	1
3.5mm Audio Out	1
3.5mm Audio In	1
Control (RS232)	1
HDMI 1.4 (with HDCP 1.4)	2
VGA In	1
VGA Out	1
Composite RCA Video In	1
Internal Speakers	10W (x1)
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	280W
Stand-by	<0.5W
Physical Controls	Keypad, Power key

On Screen Display

Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Temperature

32-104° F (0 - 40° C)

Kensington Lock Slot

1

Net (lbs)

5.1

Gross (lbs)

7.8

Net (kg)

2.3

Gross (kg)

3.5

Packaging (in.)

16.3 x 6.6 x 11.7

Physical (in.)

11.6 x 4.3 x 8.6

Packaging (mm)

415.0 x 168.0 x 297.0

Physical (mm)

294.0 x 110.0 x 218.0

Regulations

cTUVus

Package Contents

PG707W projector, power cable, VGA cable, remote control, Quick Start Guide


Warranty

*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

Recycle/Disposal

Please dispose of in accordance with local, state or federal laws.

UPC: 766907007664



4000 LUMENS and WXGA (1280x800) RESOLUTION

**Contact Sales**
ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com