





VX3211-2K-MHD - 32" 1440P IPS MONITOR WITH HDMI, DISPLAYPORT, VGA AND SRGB

Key Features


- 32 Inch QHD (2560x1440p) IPS monitor with thin bezels and 60Hz refresh rate
- Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- Optimized view settings offers “Game,” “Movie,” “Web,” “Text,” and “Mono” presets
- The VX3211-2K-MHD supports laptops, PCs, and Macs with HDMI, DisplayPort, and VGA inputs



32"
DISPLAY



IPS
PANEL



2560 x 1440
RESOLUTION



Product Description

Whether for office use or home entertainment, the ViewSonic® VX3211-2K-mhd monitor is designed to take your viewing experience to a higher level. The VX3211-2K-mhd is a 32" QHD monitor loaded with solid multimedia features, flexible connectivity options, wide-angle viewing, and amazing screen performance with 99% sRGB color coverage. Featuring stunning 2560 x 1440 resolution and a slim bezel design, this monitor provides 70% more on-screen content than Full HD monitors, making project management and multitasking easier than before. Versatile HDMI, DisplayPort, and VGA* inputs keep you connected to your favorite devices.


*VGA support for up to 1080p resolution only

Specifications

More Information	
UPC	766907918410
Screen Size	32"

Viewable Area (in.)	31.5
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	QHD (2560x1440)
Static Contrast Ratio	1,200:1
Dynamic Contrast Ratio	80M:1
Light Source	LED
Brightness	250 cd/m2
Colors	1.07B
Color Space Support	10-Bit
Aspect Ratio	16:9
Response Time (Typical GTG)	8ms
Response Time (GTG w/OD)	3ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	2560 x 1440
Mac® Resolution (max)	2560 x 1440
3.5mm Audio In	1
3.5mm Audio Out	1
VGA	1
HDMI 1.4 In	1
DisplayPort	1
Internal Speakers	2.5W (x2)
Eco Mode (Conserve)	35W
Eco Mode (optimized)	42W
Consumption (typical)	55W
Consumption (max)	65W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.3W
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1, 2, 3, 4, 5, Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104º F (0 - 40º C)

Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	24 ~ 99KHz
Frequency Vertical	24 ~ 75Hz
Analog Sync	Separate Sync / Composite Sync / Sync on Green
Digital Sync	TMDS, PCI-E
Tilt (Forward/Back)	5° / 13°
Regulations	cULus, FCC-B, ICES003, UL-MX-CoC, Mexico Energy, CE, REACH, EEL, WEEE, EAC, UkrSEPRO
Net (lbs)	15.5
Net Without Stand (lbs)	13.6
Gross (lbs)	22.6
Net (kg)	7.0
Net Without Stand (kg)	6.2
Gross (kg)	10.2
Packaging (in.)	33.0 x 24.2 x 11.1
Physical (in.)	28.7 x 19.5 x 9.1
Physical Without Stand (in.)	28.7 x 17.0 x 2.3
Packaging (mm)	838 x 615 x 282
Physical (mm)	729.7 x 495.5 x 230.0
Physical Without Stand (mm)	729.7 x 432.8 x 58.3
Package Contents	LCD Display, Power Cable , HDMI Cable , Audio Cable , Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight
UPC: 766907918410	



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com