

CDE5500-L

Perfect for use in indoor commercial environment

55" Narrow Bezel Commercial LED Display



Overview

The ViewSonic CDE5500-L is a 55" (55" viewable) commercial LED display with a 24mm narrow-bezel design that delivers more impactful visual messaging for corporate, retail, hospitality, and other indoor environments. An integrated media player supports USB-drive playback of videos, photos, and music, as well as content

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.

ViewSonic®
See the difference™ 

scheduling. In addition, it provides LAN content loading from PCs or mobile devices via network connection, offering an efficient and fast way to display content. Featuring Full HD 1080p resolution, 350-nit high brightness, 1400:1 high contrast ratio, SuperClear® technology for improved wide-angle viewing, and dual 7W stereo speakers, the CDE5500-L delivers sharp, vivid images with incredible sound for superior multimedia messaging performance. Versatile connectivity options include HDMI, DVI, D-Sub, YPbPr, and CVBS inputs for easy installation and control of a variety of high-definition devices. Integrated RS232 with IR pass-through and a one-time setting function make the CDE5500-L an easy-to-manage solution for multiple-display configurations.



Sleek, narrow bezel design for greater visual impact

**NARROW
BEZEL**

ViewSonic's CDE5500-L commercial display features a 24mm narrow bezel design. This sleek, narrow bezel maximizes impactful visual messaging for passersby, making the CDE5500-L the perfect choice for digital signage installations.



Energy-Saving LED Backlight

The CDE5500-L utilizes an energy-saving LED backlight that consumes 35% less power than conventional CCFL backlight displays. This provides for a lower overall cost of ownership, along with a higher ROI, making this display a great long-term investment.



Built-in media player for USB playback of videos, photos and music

The CDE5500-L features an integrated media player with convenient USB playback function. Now, photos, music and 1080p video can be quickly displayed on-screen directly from a USB drive – without the need for a PC.

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.






Easy LAN and wireless content streaming from PCs and mobile devices

The CDE5500-L features a RJ45 port to connect directly with PCs or notebooks via Intranet connection. This provides for the efficient loading of content onto multiple displays through a primary display. DLNA-compatible mobile devices can also utilize a wireless hub to push multimedia content directly to selected displays.



SuperClear® technology with wide viewing angles

SuperClear® image enhance technology delivers 178-degrees of vertical and horizontal viewing angles. Target audiences will experience accurate, vivid colours, and consistent brightness levels whether looking at the screen from above, below, the front, or the side—with no distortion or decay.



Full HD for Superior True-Color Performance

The ViewSonic's CDE5500-L displays content in Full HD 1920 x 1080 resolution to deliver superior pixel-by-pixel true-colour performance. At this resolution and brightness, high-definition multimedia messaging can be seen crystal-clear with a more realistic viewing experience.

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.





Normal



Full HD Resolution

RS232 Input and output for easier Management

RS232 input and output connectivity, along with IR pass-through functionality, provides for easy and efficient management of multiple-display configurations from a single notebook or PC. By using the RS232 output, daisy-chained configurations can be managed via a primary CDE5500-L display.



Efficient, user-friendly content scheduling and settings

The ViewSonic CDE5500-L commercial display provides an efficient, user-friendly scheduling interface via the on-screen display (OSD). Display setup features include time and date scheduling, repeat and shuffle settings, as well as content source settings for various inputs.



Versatile Inputs and One-Time Configuration Settings

With a versatile selection of inputs, including HDMI, DVI, CVBS, YPbPr (YCbCr) and VGA, the CDE5500-L commercial display enables you to easily connect and use a variety of analogue and digital equipment. Best of all, the one-time display installation and setup feature means your preferred source settings are never lost.



2 WATT x 2

Dual stereo speakers for enhanced audio

With a pair of integrated 7W speakers, the CDE5500-L combines eye-catching multimedia content with high-quality sound effects—creating a lasting audio-visual impression on your target audience or demographic.

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.





Portrait or Landscape Mountable

The CDE5500-L can be VESA-mounted (400mm x 400mm) in either portrait or landscape orientation for display flexibility in a variety of settings.



Technical Specifications

LCD	Size	55" (55" viewable)
	Type	TFT LED Module with LED Backlight
	Display Area	1209.6(H) x 680.4 (V) (55" diagonal)
	Optimum Resolution	1920x1080
	Contrast Ratio	1400:1 Typ.

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.



Brightness	350 cd/m2
Viewing Angles	178° horizontal, 178° vertical SuperClear®
Response Time	6ms
Aspect Ratio	16:9
Panel Surface	Hardness 3H
Colour Support	16.7M colours
Backlight	LED
Backlight Life	30,000 Hours Typ

COMPATIBILITY

RGB PC / HDMI PC	Refer to timing table
CVBS	480i
Component	480i, 480p, 720p, 1080i, 1080p
HDMI	480i, 480p, 720p, 1080i, 1080p
DVI-D	480i, 480p, 720p, 1080i, 1080p

CONNECTOR

HDMI (input)	x 1
RS-232	x 1
Audio (input/output)	x 1 (RCA L/R) / x 1 (RCA L/R)
USB	x 1
PC-VGA	x 1
Component-In	x 1
DVI	DVI-D x 1
LAN	x 1 (RJ45)
PC Audio Input	x 1 (3.5mm jack)
CVBS	(Share with component Y) x 1
IR Pass Through	x 1

CONTROLS

Picture	POWER, MUTE, INPUT, VOL +/-, UP, DOWN, MENU. Picture style, Restore style, Backlight, Contrast, Brightness, Colour, Sharpness, Advanced, Game or Computer, Format and edges
Configuration 1	Menu language, Monitor id, Eco mode, Auto search, Clock, USB scheduling, Sleep timer, Auto switch off, Control settings, Factory settings
Configuration 2	View network settings, Network configuration, Static IP configuration, Digital Media Render, Network name
Sound	Sound style, Restore style, Bass, Treble, Audio out, Advanced

POWER

Voltage	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
Consumption	109 W (typ), 128 W (max)

OPERATING CONDITIONS

Temperature	0°C to 40°C
Humidity	20% ~ 80% @40°C non-condensing

DIMENSIONS

Physical Without Stand	49.8 x 29 x 1.7 / 1264.7 x 735.5 x 42.8 (inch/mm)
Packaging	54.1 x 34.3 x 5.9 / 1374 x 870 x 150 (inch/mm)

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.



WEIGHT	Gross	56.4 / 25.6 (lb / kg)
	Net Without Stand	46.7 / 21.2 (lb / kg)
REGULATIONS		CE, CB, WEEE, C-tick, FCC, ICES003, UL/cUL, CE,CB, CU, Energy star 6.0,
PACKAGE CONTENTS		1.CDE5500-L LCD Monitor 2.Remote Control with batteries 3.User manual CD wizard 4.Quick Start Guide 5.Power Cables 6.VGA cable 7.RS232 cable *Actual content may differ from market to market
VESA® MOUNT		400 x 400mm
WARRANTY		3-year limited **Warranty offered may differ from market to market
Audio I/O	SPDIF out	x 1(optical)
	Speakers	7W x 2

ViewSonic® Limited Warranty



ViewSonic provides customers with the security of a manufacturers warranty against defected products. The type and duration of the applicable warranty service varies by product type, country of purchase and can also vary on an individual basis according to customer requirements agreed at time of purchase. The warranty will expire after the end of the warranty period.

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.

