

PJ258D

**MICRO-PORTABLE DLP®
VIEWDOCK™ PROJECTOR
WITH IPOD® DOCK FOR XXL VIDEOS**

Digital lifestyle iPod projector

ViewSonic's PJ258D ViewDock projector sets the bar for digital lifestyle projectors by converging entertainment excitement with professional practicality. The integrated iPod dock lets you PROJECT CONTENT DIRECTLY FROM YOUR IPOD WITH VIDEO for larger-than-life pictures and videos. The array of projector connectivity options allows you to connect a PC, DVD player, game consoles and more. The PJ258D uses Texas Instruments DLP technology for RAZOR SHARP DIGITAL IMAGES and brilliantly displays 2000 lumens for use in virtually any setting. Its stylishly contoured design is sophisticated enough for the contemporary mobile professional and convenient enough for the entertainment aficionado. Your projector doesn't have to be lacklustre anymore as ViewSonic's PJ258D ViewDock elevates the status of your digital lifestyle.



iPod sold separately

LIFE-SIZE YOUR IPOD

- > **Bright in virtually any setting with 2000 lumens**
Packs 2000 ANSI lumens in just 1.8kg. It's the bright choice for multimedia presenters.
- > **Life-size your iPod with video**
Dock and charge your iPod with video in the projector's docking station. Share your videos, podcasts, games and presentations in larger-than-life fashion.
- > **DLP technology**
Stunning all-digital clarity delivers lifelike colour, sharp graphics, and outstanding video.
- > **Ultimate video source flexibility**
Connect a computer or add a video source for dynamic meetings and presentations.
- > **Supports HD signals including 720p and 1080i**
Capable of displaying HD signals as well as other video and data sources¹.
- > **Easy set-up and auto-tuning**
One-touch set-up button for fast, easy sync and sharp focus.
- > **Unplug and go**
Direct off feature lets you unplug the projector and go.



ViewSonic®
See the difference™ 

PJ258D

MICRO-PORTABLE DLP® VIEWDOCK™ PROJECTOR WITH IPOD® DOCK FOR XXL VIDEOS



DLP	Type Resolution Lens Zoom Factor Digital Keystone	0.55" DDR XGA DMD DLP 1024 x 768 XGA native, (max. 1280 x 1024 SXGA compressed) Manual zoom, manual focus 1.2 (F = 2.3–2.75/f = 20.2mm–24.2mm) Vertical ± 15°
DISPLAY	Size Throw Distance Throw Ratio Lamp Brightness Contrast Ratio Aspect Ratio	40"–300" (1.01m–7.62m) (Diagonal) 1.6m–12.0m 1.64–1.96:1 200W, 2000 hours (Eco mode 3000 hours ²) 2000 ANSI lumens (typ.) 2000:1 (max.) 4:3 (native), 16:9
AUDIO	Speaker	2 watt
INPUT SIGNAL	Video Frequency	RGB analogue, Video NTSC M, NTSC 4.43, PAL (B, D, G, H, I, M, N60), SECAM (B, D, G, K, K1, L), SDTV/EDTV (480i/p, 576i/p) HDTV (720p, 1080i) F _H : 31–79.8Hz; F _V : 56–85Hz
COMPATIBILITY	PC Mac ^{®3}	Analogue: VGA up to SXGA (scaled), 1024 x 768 @ 60Hz preferred Analogue: up to SXGA (scaled), 1024 x 768 @ 60Hz preferred
CONNECTOR	PC-VGA Composite Video S-Video Component Video ViewDock Audio USB	1 x 15-pin mini D-sub 1 x RCA jack 1 x 4-pin mini-DIN 15-pin mini D-sub to 3 x RCA component video adapter (optional) iPod dock (Made for iPod certified) 1 x 3.5mm stereo mini jack USB Typ B (for service only)
POWER	Voltage Consumption	AC 100–240V, 50/60Hz (auto switch) 280W (typ.)
CONTROLS	Basic OSD ⁴	Stand-by, menu, input Display Menu (mode, brightness, contrast, white intensity, colour temperature, saturation), Management Menu (Eco mode, OSD position, OSD background, projection [rear, front], V keystone, source lock, high altitude mode, reset), Image Menu (frequency, phase, H/V position, degamma, aspect ratio, 16:9 V image position), Language Menu (English, French, German, Italian, Japanese, Portuguese, Spanish, Simplified Chinese, Traditional Chinese), colour setting, lamp setting
OPERATING CONDITIONS	Temperature Humidity	0°C–40°C 10%–90% (non condensation)
NOISE LEVEL	Normal Eco mode	37dB (typ.) 34dB (typ.)
DIMENSIONS	(W x H x D mm)	288 x 83 x 190 (physical) 332 x 315 x 195 (packaging)
WEIGHT	Net Gross	1.8kg 4.6kg
REGULATIONS		CE, CB, TÜV/GS, GOST, UL, CUL, FCC-B, CCC, PSB, NOM, WEEE, RoHS
OTHER		iPod dock, Eco mode, optical zoom, wireless remote control, soft carrying case, progressive scan, direct off for unplug and go, daylight mode
PACKAGE CONTENTS		DLP Projector, power cables (Europe [Schuko]/UK), VGA cable, composite cable, remote control, batteries, lens cap, soft carrying case, Quick Start Guide (multi-language), ViewSonic Wizard CD (User guide) (multi-language)
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

OPTIONAL ACCESSORIES

- > Replacement lamp RLC-025
- > Soft case with wheels and laptop bag CASE-006
- > VGA to component video adapter ADPT-002
- > Wireless G Presentation Gateway WPG-100



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



ViewSonic Europe Limited/UK

Riverside House
7th Floor
2a Southwark Bridge Road
London, SE1 9HA
United Kingdom

Tel: +44 (0) 207 921 2200
Fax: +44 (0) 207 921 2201

ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France

Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation

381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux

ViewSonic Denmark
ViewSonic Finland
ViewSonic Italy
ViewSonic MEA
ViewSonic Netherlands
ViewSonic Norway
ViewSonic Spain
ViewSonic Sweden

Tel: +32 (0)56 85 26 27
Tel: +45 70 22 11 71
Tel: +358 20 7120 860
Tel: +39 02 73 95 50 22
Tel: +971 (0) 4 88 11 871
Tel: +31 (0)20 491 9254
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ Optional cables required. ² Running Eco mode exclusively can extend lamp life up to 3000 hours. ³ May require optional Mac adapter. ⁴ Some features may not be available on all inputs.