

ViewSonic® VA721 LCD Display

17" LCD DISPLAY



The Right Choice: Attractive Styling in a Super-slim LCD.

The ViewSonic VA721 LCD display not only brings images to life with vivid colour and outstanding realism. Its stylish design is also sure to catch your eye. The fold-up base makes wall mounting a breeze, letting you reclaim long-lost desk space. Delivering ViewSonic's renowned image quality, the VA721 enhances your viewing comfort with high brightness and progressive styling. Get the LCD display with perfect looks - the ViewSonic VA721!

Fun, Style and Comfort

... UltraBrite™ Technology

UltraBrite™ technology enables optimised viewing of video and graphics applications. Games, TV and DVDs come alive with rich, saturated colour and vivid contrast. Precise definition and photo-realistic image quality boost 3-D video and professional graphics

... Full 17.0" Viewable Screen

... 1280 x 1024 Optimum Resolution

... OSD/Power Lock Function

When activated, the user-controlled OSD/Power lock function prevents changes to monitor settings, maintaining an optimised image.

... Fold Up 90° Base For Wall Mounting®

The compact base folds up 90° for VESA-compliant wall mounting, making conversion between desktop and wall mount applications easy.

... OnView Controls Including ViewMatch Technology

Screen adjustments are made via an on-screen menu using simple controls. This user-friendly control system allows easy adjustments of image quality, size, position and geometry for optimal viewing.

... AutoTune™ Function

Provides the best image by monitoring signals from the computer and automatically optimising the monitor settings.

... ViewSonic Wizard

This software provides user-friendly installation.

... TCO'99 and Energy Certified

This LCD display complies with one of the world's strictest standards for low emissions, safety, ergonomics, recycling and power management while saving costs through automatic power saving modes.

... 300 cd/m² brightness (typ) and 500:1 contrast ratio (typ) for rich, detailed images.

... sRGB colour Management

For a closer match of image display to print outs.

ViewSonic® 
the choice of professionals

Image

ViewSonic® VA721 LCD Display

17" LCD DISPLAY



17.0" LCD DISPLAY WITH ONVIEW® CONTROLS

LCD PANEL	Type	17" Colour TFT Active Matrix SXGA LCD, TN Technology.
	Display Area	337.9mm horizontal x 270.3mm vertical
	Contrast Ratio	500:1 (typ)
	Viewing Angles	140° horizontal, 130° vertical @ 10:1 170° horizontal, 170° vertical @ 5:1
	Response Time	16ms (typ)
	Brightness	300 cd/m ² (typ)
	Panel Surface	Anti-glare
VIDEO INPUT	Analogue	RGB Analogue (75 ohms, 0.7 Vp-p)
	Frequency	F _H : 30~80kHz, F _V : 50~85Hz
	Sync	H/V separated (TTL)
COMPATIBILITY	PC	VGA up to 1280x1024 (non interlaced)
	Mac^{®1}	Power Mac™ G3/G4 up to 1280x1024
CONNECTOR	Signal	15-pin mini D-sub, attached cable
	Power	3-pin AC plug
POWER	Voltage	AC 100~240V, 50~60Hz (internal power supply)
	Consumption	< 30W (typ)
USER CONTROLS	Basic	Power (Soft), [1], [Down], [Up], [2]
	OSD	Auto Image Adjust, Contrast, Brightness, Colour Adjust [sRGB, 9300K, 6500K (default), 5400K, R, G, B], Information [Mode, Model Number, Serial Number, Website], Manual Image Adjust [H. Size, H. Position, V. Position, Fine Tune, Sharpness, Setup Menu Language (English, French, German, Italian, Spanish, Finnish, Japanese, Simplified and Traditional Chinese), Resolution Notice, OSD Position, OSD Timeout, OSD Background], Memory Recall
OPERATING CONDITIONS	Temperature	0~40°C
	Humidity	10~90% (non-condensing)
DIMENSIONS	Physical	377.6mm (W) x 195.6 mm (D) x 374.0 mm (H)
WEIGHT	Net	4.5 kg
REGULATIONS		TCO'99, TÜV/GS, TÜV/Ergo, TÜV-S, ISO13406-2 (class 2), UL, c-UL, IC-B, CB Report, CE, FCC-B, BSMI, VCCI, PSB, PCBC, EPA, NOM, C-TICK, GOST-R, PCT, CCC, EnergyStar, ENERGY, Taiwan Green mark
POWER MANAGEMENT		Meets TCO, ENERGY STAR and ENERGY standards.
WARRANTY		Please see: http://www.viewsoniceurope.com/UK/Support/warranty.htm

Specifications



ISO 9001



FM 40187

ISO 14001



EMS 40968

ViewSonic Corporation's QMS/EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.

ViewSonic®



the choice of professionals

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux
ViewSonic Denmark
ViewSonic Finland
ViewSonic Italy
ViewSonic MEA
ViewSonic Norway
ViewSonic Spain
ViewSonic Sweden

Tel: +32 056/85 26 27
Tel: +45 70 22 11 71
Tel: +358 (9) 54 06 40 70
Tel: +39 02 5832 0356
Tel: +971 (0) 4 88 11 871
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹Adapter may be required. Specifications subject to change without notice. Selection, offers and programmes may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2005 ViewSonic Corporation. All rights reserved. VA721 04/05-UK

For more product information, visit us on the web at www.ViewSonicEurope.com