

VA916

19" LCD MONITOR VA SERIES

WITH 5MS VIDEO RESPONSE TIME

Affordable big screen LCD

ViewSonic's 19" VA916 LCD monitor offers an exciting array of features DESIGNED TO ENHANCE YOUR WORK AND PLAY with minimal impact on your wallet. With a 2000:1 DYNAMIC CONTRAST RATIO (typ.) and 300cd/m² brightness (typ.), you can work comfortably for hours. The stylish, slim bezel saves space and lets you reclaim valuable desktop real estate, while the wide viewing angles give you an excellent picture from nearly every angle. The latest generation OSD/power lock and AutoTune® functions maximise and maintain your display settings. The Vista-approved VA916 is a stylish upgrade for your home office that helps you stay within your budget.

It's not just another LCD monitor. It's a ViewSonic.



FEATURE-RICH, STYLISH DESIGN

- > **2000:1 Dynamic Contrast Ratio**
Provides for darker black levels and better overall front-of-screen performance.
- > **Super fast 5ms video response delivers superior picture clarity**
- > **Full 19" viewable screen**
Displays a full, flat 19" viewable area with crisp detail and fully saturated colour.
- > **1280 x 1024 native resolution**
Incredible image detail for sharp text and graphics.
- > **Stylish slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OSD/power lock secures your settings**
Prevents changes to monitor settings and maintains an optimised image.
- > **OnView® controls for superior screen adjustability**
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **Integrated power supply**
- > **Windows Vista approved**
- > **ViewSonic Wizard included**
User-friendly Wizard software automates the setup process to deliver optimised screen performance.
- > **PC and Mac® compatible**
- > **TCO'03 and ENERGY STAR® qualified**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference™ 

VA916

19" LCD MONITOR VA SERIES WITH 5MS VIDEO RESPONSE



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

LCD	Type	19" TN colour TFT active matrix SXGA LCD	
	Display Area	37.6cm horizontal x 30.1cm vertical, 48.3 cm diagonal	
	Pixel Pitch	0.294mm	
	Optimum Resolution	1280 x 1024@60Hz	
	Pixel Clock	140MHz	
	Contrast Ratio	1000:1 (typ.), 2000:1 DCR (typ.)	
	Viewing Angle	170° horizontal, 160° vertical (at 10:1) 170° horizontal, 170° vertical (at 5:1)	
	Response Time	5ms (off-on-off) (typ.)	
	Colour Support	16.7M colours supported (6-bit + 2-bit FRC)	
	Light Source	Long life, 40000 (typ.)	
Brightness	300cd/m ²		
Panel Surface	Anti-glare		
VIDEO INPUT	Analogue	RGB analogue (0.7/1.0 Vp-p, 75 ohm)	
	Frequency	F _H : 30–82kHz, F _V : 50–75Hz	
	Synchronisation	H/V separate (TTL)	
COMPATIBILITY	PC	VGA up to 1280 x 1024 non-interlaced	
	Mac ¹	Power Mac™ up to 1280 x 1024 non-interlaced	
CONNECTOR	Analogue	15-pin mini D-Sub (detachable cable)	
	Power	3-pin AC plug (CEE22)	
POWER	Voltage	AC 100–240V, 50/60Hz (auto switch), internal power supply	
	Consumption	32 watt (typ.), <1 watt in power save mode	
ERGONOMICS	Tilt	Down 5°, Up 20°	
CONTROLS	Basic	Power, menu [1], up, down, select [2]	
	OSD	Auto image adjust, contrast, brightness, ViewMatch® colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), auto white balance, OSD/power lock, memory recall	
OPERATING CONDITIONS	Temperature	0°C–40°C	
	Humidity	10%–90% (non-condensation)	
DIMENSIONS	(W x H x D mm)	412 x 435 x 194 (with stand) 412 x 355 x 64 (without stand) 470 x 510 x 140 (packaging)	
	WEIGHT	Net	3.8kg (with stand), 3.3kg (without stand)
		Gross	5.0kg
REGULATIONS		TCO'03, TÜV/GS, TÜV/ERGO, ISO 13406-2 (pixel failure class II), CE, CB, GOST-R, Hygienic (20 copies), UL, cUL, FCC-B (ICES), ICES-003B, NOM, SASO, ENERGY, ENERGY STAR, C-Tick, KTL/MIC, BSMI, PSB, MPR II, TÜV-S, CCC, VCCI, WEEE, RoHS	
POWER MANAGEMENT		TCO'03 and ENERGY STAR standards	
SECURITY		Kensington security port	
WALL MOUNT		VESA FDMI 100mm x 100mm	
PACKAGE CONTENT		LCD Monitor, power cable, 15-pin VGA video cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)	
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm	

ViewSonic Europe Limited/UK

Riverside House
7th Floor
2a Southwark Bridge Road
London, SE1 9HA
United Kingdom

Tel: +44 (0) 207 921 2200
Fax: +44 (0) 207 921 2201

ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France

Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation

381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux

ViewSonic Denmark

ViewSonic Finland

ViewSonic MEA

ViewSonic Netherlands

ViewSonic Norway

ViewSonic Spain

ViewSonic Sweden

Tel: +32 (0)56 85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)20 7120 860
Tel: +971 (0) 4 88 11 871
Tel: +31 (0)20 491 9254
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ May require optional Mac adapter.