

VA926-LED

19" Native 4:3 LED Display

Eco-Friendly and Performance Enhancing 4:3 LED Display



Overview

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.

ViewSonic[®]
See the difference™ 

The ViewSonic VA926-LED display, equipped with ViewSonic's exclusive ClearMotiv® II imaging technology, delivers 5ms fast video response for the clearest image available. Along with a high 10,000,000:1 dynamic contrast ratio, defining a stunning level of dark and white separation, and colour depth, the built-in sRGB colour calibration maximizes colour performance. Versatile input options, including DVI-D and VGA. Equipped with a VESA-mountable design, the display can be mounted on a wall or any VESA-compliant monitor stand. LED backlight modules and ViewSonic's proprietary ECO mode which conserve up to 50% energy consumption makes VA926-LED a perfect choice for home, offices and education sectors.



Eco-Mode Conserves More Energy

ViewSonic's proprietary Eco-mode function is built into all LED displays, offering options to "Optimize (75%)" or "Conserve (50%)". Both modes reduce display brightness and conserve up to 50%* energy. Especially in a low ambient light, Eco-mode adjusts brightness and improves visibility while reducing eye fatigue and prolonging the display's lamp life. With Eco-mode, lamp replacement expenditures are reduced while practicing eco-friendliness.



10M:1 DCR

10,000,000:1 MEGA Dynamic Contrast Ratio

Dynamic contrast ratio defines a differentiating relationship between darkest and brightest colours when reproducing an image. With dynamic contrast ratio, VA926-LED is capable of automatically detecting the brightness and darkness of an image and adjusts the LED backlight accordingly. It maximizes grayscale and colour ranges and boosts contrast ratio to an ultrahigh 10,000,000:1, resulting in rich, vibrant visuals.



Planet-Friendly Mercury-Free LED Backlighting

LED backlighting enhances display performance, delivers an outstanding colour range, and adjusts contrast ratios for remarkably detailed images. The mercury free LED backlighting further conserves more energy when compared to conventional displays to allow a slimmer profile and a most pleasing viewing experience.



sRGB

Reviving Colour with sRGB Colour Correction Technology

Accurate and consistent colour performance is essential for professionals in graphic design, video editing, and other professional environments. With built-in sRGB colour correction technologies, the VA926-LED series reproduces 100% sRGB rich colour performance and captures images in their original and true colours.

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.



Technical Specifications

LCD	Type	48.3cm / 19" 4:3 LED
	Display Area	37.6cm / 14.8" horizontal x 30.1cm / 11.9" vertical
	Optimum Resolution	1280x1024
	Contrast Ratio	1000:1 (typ.)
	Brightness	250 cd/m2 (typ.)
	Viewing Angles	170° horizontal, 160° vertical
	Response Time	5ms (typ)
	Dynamic Contrast Ratio	10,000,000:1
COMPATIBILITY	PC	PC compatibles (VGA up to 1280x1024 non-interlaced)
	Mac®	Up to 1280x1024
CONNECTOR	Analog	VGA
	Digital	DVI-D
ERGONOMICS	Tilt	Forward 5°, Back 20°
CONTROLS	OSD	Auto Image Adjust, Contrast/Brightness, Color Adjust (sRGB, Bluish, Cool, Native, Warm, User Color [R,G,B]), Information, Manual Image Adjust (H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Aspect Ratio, Eco-mode), Setup Menu (Language Select, Resolution Notice, OSD Position, OSD Timeout, OSD Background, Auto Power Off, Power Indicator), Memory Recall
	Front Panel	Power, 1, up, down, 2
POWER	Consumption	18W (typ)
	Eco Mode	Optimize: 16W (typ) Conserve: 12W (typ)
DIMENSIONS	Physical With Stand	16.2 x 17.1 x 7.7 in. / 412.2 x 434.9 x 195 mm
	Physical Without Stand	16.2 x 14.0 x 2.5 in. / 412.2 x 354.9 x 63.8 mm
	Packaging	18.5 x 20.1 x 5.5 in. / 470 x 510 x 140 mm
WEIGHT	Gross	10.8 lb. / 4.9 kg

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.



Net With Stand 7.7 lb. / 3.5 kg
Net Without Stand 6.9 lb. / 3.1 kg

REGULATIONS

CE, CB, CU, UkrSEPRO, Windows, UL, cUL, FCC-B / ICES-003B, WEEE, RoHS, ENERGY STAR®, REACH SVHC List, TCO 5.0

VESA® MOUNT

100x100 mm

ViewSonic® Limited Warranty

ViewSonic provides customers with the security of a manufacturer's warranty against defected products. The type and duration of the applicable warranty service varies by product type, country of purchase and can also vary on an individual basis according to customer requirements agreed at time of purchase. The warranty will expire after the end of the warranty period.

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.

