

VA703m

**17" VA SERIES LCD MONITOR
WITH MULTIMEDIA**

High quality, high performance

The 17" ViewSonic VA703m is the all-in-one price performance solution for all needs. No matter if your use is for entertainment or for intensive graphics, whether in the home or in the office, the VA703m fits the bill perfectly. Its 5ms response time delivers crisp images and fluid full-motion video for games, movies and scrolling-text. Matched with 700:1 contrast levels and 300cd/m² brightness, the VA703m displays brilliant, vivid, true-to-life colours. Invisible built-in speakers deliver true multimedia performance. The slim styling and silver-black bezel add to the monitors appeal. Prepare to be impressed by the performance, quality and style of the VA703m.

It's not just a great value LCD. It's a ViewSonic.



IMPRESSIVE PERFORMANCE WITHOUT THE HIGH PRICE TAG

- > **ClearMotiv™ 5ms video response time**
Super fast 5ms video response delivers broadcast-quality full motion video.
- > **Multimedia enhanced**
Save workspace and enjoy rich sound with built-in invisible stereo speakers.
- > **High brightness and contrast**
300cd/m² brightness (typ.) and 700:1 contrast ratio (typ.) for clear, detailed images.
- > **Full 17" – Viewable screen with 1280 x 1024 resolution**
Displays a full, flat 17" viewable area with crisp details and fully saturated colours.
- > **Stylish slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OnView® controls for superior screen adjustability**
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **OSD/Power lock secures your settings**
Prevents changes to monitor settings and maintains an optimised image.
- > **Integrated power supply**
- > **VESA® 100mm wall mount interface and Kensington® security port**
- > **PC and Mac® compatible**
- > **TCO'03 and ENERGYSTAR® qualified**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES



ViewSonic®
See the difference™ 

VA703m

17" VA SERIES LCD MONITOR WITH MULTIMEDIA



| | | |
|-----------------------------|--------------------|--|
| LCD | Type | 17" TN colour TFT active matrix XGA LCD |
| | Display Area | 33.8cm horizontal x 27.0cm vertical; 43.2cm diagonal |
| | Pixel Pitch | 0.264mm |
| | Optimum Resolution | 1280 x 1024@60Hz |
| | Pixel Clock | 135MHz |
| | Contrast Ratio | 700:1 (typ.) |
| | Viewing Angles | 160° horizontal, 160° vertical (at 10:1) 170° horizontal, 170° vertical (at 5:1) |
| | Response Time | 5ms (off-on-off) (typ.) |
| | Colour Support | 16.7M colours supported (6-bit+2-bit FRC) |
| | Light Source | Long life, 50000 hrs. (min.) |
| | Brightness | 300cd/m ² (typ.) |
| | Panel Surface | Anti-glare (3H) |
| VIDEO INPUT | Analogue | RGB analogue (0.7 Vp-p, 75 ohm) |
| | Frequency | F _v : 30 – 82kHz, F _s : 50 – 75Hz |
| | Synchronisation | H/V separate (TTL) |
| COMPATIBILITY | PC | VGA up to 1280 x 1024 non-interlaced (@60Hz preferred) |
| | Mac ^{®1} | Power Mac™ up to 1280 x 1024 non-interlaced (@60Hz preferred) |
| CONNECTOR | Analogue | 15-pin mini D-Sub (attached cable) |
| | Audio | 3.5mm stereo audio line-in |
| | Power | 3-pin AC plug (CEE22) |
| AUDIO | Speakers | 2 x 1 watt integrated invisible stereo speakers |
| POWER | Voltage | AC 100 – 240V, 50/60Hz (auto switch), internal power supply |
| | Consumption | 36 watt (max.), <1 watt in power save mode |
| ERGONOMICS | Tilt | Down 5°, Up 20° |
| CONTROLS | Basic | Power, menu [1], up, down, select [2] |
| | OSD | Auto image adjust, contrast, brightness, audio adjust (volume, mute), ViewMatch® colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number, website), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language [English, Finnish, French, German, Italian, Japanese, Spanish, Simplified Chinese, Traditional Chinese], resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall |
| OPERATING CONDITIONS | Temperature | 0°C – 40°C |
| | Humidity | 10% – 90% (non-condensation) |
| DIMENSIONS | (W x H x D mm) | 379 x 400 x 210 (with stand) |
| WEIGHT | Net | 3.6kg (with stand) |
| | Gross | 4.8kg |
| REGULATIONS | | TCO'03, CE, CB, TÜV/GS, TÜV/Ergo, ISO13406-2 (pixel failure class II), UL/cUL, FCC-B, NOM, GOST-R, ENERGY STAR, BSMI, CCC, (PSB), (C-TICK), Green Mark, WEEE, RoHS |
| POWER MANAGEMENT | | Meets TCO'03 and ENERGY STAR standards |
| SECURITY | | Kensington® security port |
| WALL MOUNT | | VESA FDMI 100mm x 100mm |
| PACKAGE | | LCD Monitor, power cable, audio cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) |
| WARRANTY | | Please see: www.viewsoniceurope.com/UK/Support/warranty.htm |

ViewSonic Europe Limited/UK

Riverside House
7th Floor
2a Southwark Bridge Road
London, SE1 9HA
United Kingdom

Tel: +44 (0) 207 921 2200
Fax: +44 (0) 207 921 2201

ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France

Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation

381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux

ViewSonic Denmark

ViewSonic Finland

ViewSonic MEA

ViewSonic Netherlands

ViewSonic Norway

ViewSonic Spain

ViewSonic Sweden

Tel: +32 (0)56 85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)20 7120 860
Tel: +971 (0) 4 88 11 871
Tel: +31 (0)20 491 9254
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ May require optional Mac adapter.